

ALT950

AL/ALT



GEHL®

Capacities		Imperial
Static tipping load with forks (straight)		10975 lb
Static tipping load with forks (full turn)		9143 lb
Max. payload with forks as per EN 474-3 (80%)		7275 lb
Max. lifting height (below forks)	h3	17 ft 1 in
Max. outreach		10 ft 10 in
Reach at max. height		3 ft 11 in
Breakout force with bucket		6730 daN
Static tipping load with pallet forks - Straight with cab		10975 lb
Weight and dimensions		
Unladen weight (with forks)		18717 lb
Overall length to carriage (with hitch)	l11	18 ft 9 in
Wheelbase	y	8 ft 2 in
Overall height with cab	h17	8 ft 10 in
Tilt-up angle	a4	9 °
Tilt-down angle	a5	156 °
External turning radius (over tyres)	Wa1	13 ft 9 in
Articulation angle	a19	44 °
Overall width less bucket	b1	7 ft 6 in
Overall length - Less Bucket	l2	18 ft 9 in
Standard tires		Alliance - A580 - 460/70 R24 159A8
Ground clearance	m4	1 ft 3 in
Performances		
Crowd		3.50 s
Dump		2.70 s
Engine		
Engine brand		Deutz
Engine model		TCD 4.1 L4
Engine norm		Tier 4
Number of cylinders / Capacity of cylinders		4 - 246 in ³
I.C. Engine power rating / Power		143 Hp / 105 kW
Max. torque / Engine rotation		406 ft/lbs / 2300 rpm
Engine cooling system		3 radiators water + intercooler + hydraulic oil
Transmission		
Transmission type		M-Varioshift
Max. travel speed (may vary according to applicable regulations)		25 mph
Travel speed (laden)		25 mph
Differential lock		Limited slip differential on front and rear axles
Parking brake		Manual
Hydraulics		
Hydraulic pump type		Variable displacement pump
Hydraulic flow - Pressure		42 US gpm / 3916 PSI
Tank capacities		
Hydraulic oil		40 US gal
Fuel tank		40 US gal
Diesel Exhaust fluid (AdBlue® type)		3 US gal
Noise and vibration		
Noise at driving position (LpA) tested following NF EN 12053 norm		72 dB
Noise to environment (LwA)		107 dB
Vibration to whole hand/arm		< 2.52 m/s ²
Miscellaneous		
Safety cab homologation		ROPS - FOPS level 2 cab



Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend