ALT950 AL/ALT



GEHL®

	ALT950 Creado	el 17 de mayo de 2024, 12:20:32 UT
Capacities		Métrico
Static tipping load with forks (straight)		4978 kg
Static tipping load with forks (full turn)		4147 kg
Max. payload with forks as per EN 474-3 (80%)		3300 kg
Max. lifting height (below forks)	h3	5.20 m
Max. outreach		3.30 m
Reach at max. height		1.20 m
Breakout force with bucket		6730 daN
Static tipping load with pallet forks - Straight with cab		4978 kg
Weight and dimensions		
Unladen weight (with forks)		8490 kg
Overall length to carriage (with hitch)	l11	5.72 m
Wheelbase	у	2.50 m
Overall height with cab	h17	2.70 m
Tilt-up angle	a4	9°
Tilt-down angle	a5	156 °
External turning radius (over tyres)	Wa1	4.20 m
Articulation angle	a19	44 °
Overall width less bucket	b1	2.29 m
Overall length - Less Bucket	12	5.72 m
Standard tires		Alliance - A580 - 460/70 R24 159A8
Ground clearance	m4	0.39 m
Performances		0.32 111
Crowd		3.50 s
Dump		2.70 s
Engine Company		2.703
Engine brand		Deutz
Engine model		TCD 4.1 L4
Engine norm		Tier 4
Number of cylinders / Capacity of cylinders		4 - 4038 cm ³
I.C. Engine power rating / Power		143 Hp / 105 kW
Max. torque / Engine rotation		550 Nm / 2300 rpm
Engine cooling system		3 radiators water + intercooler + hydraulic oil
Transmission		3 radiators water - intercooler - riyuradiic oit
Transmission type		M-Varioshift
Max. travel speed (may vary according to applicable regulations)		40 km/h
Travel speed (laden)		40 km/h
Differential lock		Limited slip differential on front and rear axles
Parking brake		Manual
Hydraulics		ividii u at
		Variable displacement pump
Hydraulic pump type Hydraulic flow - Pressure		variable displacement pump 158 l/min / 270 bar
		158 t/IIIIII / 270 bar
Tank capacities		450.1
Hydraulic oil		150 l
Fuel tank Discal Exhaust fluid (AdRius® tups)		150 l
Diesel Exhaust fluid (AdBlue® type) Noise and vibration		10 l
		70 dp
Noise at driving position (LpA) tested following NF EN 12053 norm		72 dB
Noise to environment (LwA)		107 dB
Vibration on hands/arms		< 2.52 m/s²
Miscellaneous		
Safety cab homologation		ROPS - FOPS level 2 cab





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend