

# AL430

ARTICULATED LOADERS



## Key Features

- ✓ 4-Post Open Canopy ROPS and FOPS Certified
- ✓ Front Auxiliary Hydraulics with Flat-Faced Couplers
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Automotive Style Hydrostatic Drive, 2-Speed
- ✓ Perkins Turbo Charged Diesel Engine
- ✓ Deluxe, Tilttable Steering Column
- ✓ Multi-Function Joystick

## SPEZIFIKATIONEN

		METRISCH
Capacities	Static tipping load with bucket (straight)	1540 kg
	Static tipping load with bucket (full turn)	1355 kg
	Static tipping load with forks (straight)	1175 kg
	Static tipping load with forks (full turn)	1030 kg
	Max. height of bucket pivot point	2.83 m
Weight and dimensions	Unladen weight (with forks) with 4-post canopy	2316 kg
	Wheelbase	1.65 m
	Overall cab width	0.99 m
	Overall height with 4 posts canopy	2.25 m
	Dump reach - Full height	479 mm
	Hood Height	1.40 m
	Overall Operating Height - Fully Raised	3.63 m
	Articulation angle	45 °
	Maximum oscillation angle	11 °
	Overall length with bucket	4.27 m
	Overall width less bucket	1.10 m
	Overall length - Less Bucket	3.58 m
	Rear overhang	1.12 m
	Dump angle - Fully raised	42 °
	Dump Height - Fully Raised	2.12 m
	Maximum Rollback Angle - Fully Raised	48 °
	Digging Position	-79 mm
	Ground clearance	320 mm
	Clearance Radius - Front with Bucket	3.24 m
	Clearance Radius - Less bucket	2.77 mm
	Ground Plane to Bucket Edge Height	2.65 m
	Tread width (wheel center)	836 mm
	Attachment Pivot Clearance	103 mm
Height from ground to axle center	214 mm	
Bucket Width	1.52 m	
Front Wheel Center to Pivot Pin	0.66 m	
Height to Hinge Pin - Fully Raised	2.90 m	
Engine	Engine brand	Perkins
	Engine model	403J-17T
	Engine norm	Stage V
	Number of cylinders	3
	I.C. Engine power rating / Power	48.90 Hp / 36 kW
Max. torque / Engine rotation	160 Nm / 1600 rpm	
Engine cooling system	Water	
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	20 km/h
	Max. travel speed (in option) (may vary according to applicable regulations)	30 km/h
	Travel speed (laden)	20 km/h
	Parking brake	Mechanical hand-operated parking brake
Service brake	Hydraulic drum brake on front axle, acting on all 4 wheels	
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	60 l/min / 207 bar
	Drive hydraulic system pressure	207 bar
Tank capacities	Hydraulic oil	48 l
	Fuel tank	50 l



## STANDARDMERKMALE

- Counterweight
- Inching Pedal
- Instrument Panel - Deluxe
- Hydrostatic Drive - Servo
- Tilttable, Deluxe Steering Column
- Adjustable 2-inch Seat Belt
- Lockable Engine Cover and Fuel Cap
- Horn
- Combination Radiator & Hydraulic Oil Cooler
- Adjustable Seat 5-Way
- Additional Set of Front Auxiliary Hydraulics
- Battery Disconnect

## OPTIONALE MERKMALE

- led front road lights
- Differential Lock
- LED Work Lights
- Air suspension seat
- Cabin with Heat and Air Conditioning

® bezeichnet die Eintragung in den Vereinigten Staaten. Marken können in anderen Ländern registriert sein oder auch nicht.



One Gehl Way, West Bend, WI 53095  
Telefon: (262) 334-9461



GEHL COMPACT EQUIPMENT