AL530 AL/ALT



GEHL®

		ani 2. Mai 2024 uni 13.39.10 01C
Capacities		Metrisch
Static tipping load with bucket (straight)		1880 kg
Static tipping load with bucket (full turn)		1650 kg
Static tipping load with forks (straight)		1470 kg
Static tipping load with forks (full turn)		1295 kg
Max. height of bucket pivot point	h35	3.07 m
Weight and dimensions		
Unladen weight (with forks) with 4-post canopy		2678 kg
Wheelbase	у	1.77 m
Overall cab width	b4	0.99 m
Overall height with cab	h17	2.29 m
Dump reach - Full height	r6	458 mm
Hood Height	h40	1.46 m
Overall Operating Height - Fully Raised	h27	3.87 m
Articulation angle	a19	40 °
Maximum oscillation angle		10 °
Overall length with bucket	l16	4.49 m
Overall width less bucket	b1	1.33 m
Overall length - Less Bucket	l2	3.79 m
Rear overhang	 c6	1.14 m
Dump angle - Fully raised	a5	47 °
Dump Height - Fully Raised	h29	2.30 m
Maximum Rollback Angle - Fully Raised	a4	46 °
Maximum Rollback Angle at Ground	a13	50 °
Digging Position	h32	-72 mm
Ground clearance	m4	356 mm
Clearance Radius - Front with Bucket	b18	3.36 m
Clearance Radius - Less bucket	b14	2.88 m
Ground Plane to Bucket Edge Height	h42	2.83 m
Tread width (wheel center)	b29	946 mm
	029	168 mm
Attachment Pivot Clearance	··· 0	230 mm
Height from ground to axle center	m8	
Bucket Width	e1	1.52 m
Front Wheel Center to Pivot Pin	m3	733 mm
Height to Hinge Pin – Fully Raised	h28	3.07 m
Engine		D. 1.
Engine brand		Perkins
Engine model		403J-E17T
Engine norm		Stage V
Number of cylinders		3
I.C. Engine power rating / Power		48.90 Hp / 36 kW
Max. torque / Engine rotation		160 Nm / 1600 rpm
Engine cooling system		Water
Transmission		
Transmission type		Hydrostatic
Number of gears (forward / reverse)		2 / 2
Max. travel speed (may vary according to applicable regulations)		20 km/h
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow - Pressure		60 l/min / 207 bar
Drive hydraulic system pressure		207 bar
Tank capacities		
Hydraulic oil		48 l
Fuel tank		65 l





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend