

AL550

AL/ALT



GEHL®

Capacities		Metric	Imperial
Static tipping load with bucket (straight)		2190 kg	4828 lb
Static tipping load with bucket (full turn)		1693 kg	3732 lb
Static tipping load with forks (straight)		1547 kg	3411 lb
Static tipping load with forks (full turn)		1204 kg	2654 lb
Max. height of bucket pivot point	h35	3.16 m	10 ft 4 in
Reach at max. height		0.43 m	1 ft 5 in
Breakout force with bucket		4329.46 daN	4329.46 daN
Static tipping load with bucket - Straight with cab		2190 kg	4828 lb
Static tipping load with bucket - Full turn with cab		1693 kg	3732 lb
Static tipping load with pallet forks - Straight with cab		1547 kg	3411 lb
Weight and dimensions			
Unladen weight (with forks) with 4-post canopy		3388.30 kg	7470 lb
Overall length to carriage (with hitch)	l11	4.18 m	13 ft 9 in
Wheelbase	y	1.74 m	5 ft 9 in
Overall width of 4 posts canopy	b22	1.23 m	4 ft
Overall cab width	b4	1.22 m	4 ft
Overall height with 4 posts canopy	h38	2.31 m	7 ft 7 in
Overall height with cab	h17	2.31 m	7 ft 7 in
Tilt-up angle	a4	39.90 °	39.90 °
Tilt-down angle	a5	44.70 °	44.70 °
External turning radius (over tyres)	Wa1	3.20 m	10 ft 6 in
Articulation angle	a19	45 °	45 °
Overall width less bucket	b1	1.47 m	4 ft 10 in
Ground clearance	m4	0.25 m	10 in
Performances			
Crowd		2.52 s	2.52 s
Dump		1.85 s	1.85 s
Engine			
Engine brand		Deutz	Deutz
Engine model		TD 2.2 L3	TD 2.2 L3
Engine norm		Stage V / Tier 4 Final	Stage V / Tier 4 Final
Number of cylinders / Capacity of cylinders		3 - 337.82 cm³	3 - 21 in³
I.C. Engine power rating / Power		60 Hp / 45.50 kW	60 Hp / 45.50 kW
Max. torque / Engine rotation		200 Nm / 2400 rpm	148 ft/lbs / 2400 rpm
Engine cooling system		2 radiators water + hydraulic oil	2 radiators water + hydraulic oil
Transmission			
Transmission type		Hydrostatic	Hydrostatic
Number of gears (forward / reverse)		2 / 2	2 / 2
Max. travel speed (may vary according to applicable regulations)		28.32 km/h	18 mph
Differential lock		Front and rear locking of the machine	Front and rear locking of the machine
Parking brake		Manual	Manual
Hydraulics			
Hydraulic pump type		Gear pump	Gear pump
Hydraulic flow - Pressure		58.30 l/min / 210 bar	15 US gpm / 3046 PSI
High-Flow Option (l/min)		72.30 l/min	19 US gpm
Drive hydraulic system pressure		420 bar	6092 PSI
Tank capacities			
Hydraulic oil		45 l	12 US gal
Fuel tank		82.50 l	22 US gal
Miscellaneous			
Safety cab homologation		ROPS - FOPS level 1 cab	ROPS - FOPS level 1 cab



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend