

AL650

AL/ALT



GEHL®

Capacities		Imperial
Static tipping load with bucket (straight)		6744 lb
Static tipping load with bucket (full turn)		4916 lb
Static tipping load with forks (straight)		5302 lb
Max. height of bucket pivot point	h35	10 ft 11 in
Max. lifting height (below forks)	h3	10 ft 3 in
Breakout force with bucket		5743 daN
Weight and dimensions		
Unladen weight (with forks) with 4-post canopy		9149 lb
Wheelbase	y	79 in
Overall width of 4 posts canopy	b22	4 ft 6 in
Overall cab width	b4	4 ft 6 in
Overall height with 4 posts canopy	h38	8 ft 1 in
Overall height with cab	h17	8 ft 1 in
Tilt-up angle	a4	45 °
Tilt-down angle	a5	45 °
External turning radius (over tyres)	Wa1	10 ft 10 in
Articulation angle	a19	45 °
Overall width less bucket	b1	5 ft 5 in
Overall length - Less Bucket	l2	14 ft
Ground clearance	m4	1 ft 3 in
Engine		
Engine brand		Yanmar
Engine model		4TNV98CT
Engine norm		Tier 4 final
Number of cylinders / Capacity of cylinders		4 - 201 in ³
I.C. Engine power rating / Power		64.40 Hp / 48 kW
Max. torque / Engine rotation		207 ft/lbs / 2300 rpm
Engine cooling system		2 radiators water + hydraulic oil
Transmission		
Transmission type		Hydrostatic
Number of gears (forward / reverse)		2 / 2
Max. travel speed (may vary according to applicable regulations)		19 mph
Travel speed (laden)		19 mph
Differential lock		Front and rear locking of the machine
Parking brake		Manual
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow - Pressure		18 US gpm / 2901 PSI
High-Flow Option (l/min)		26 US gpm
Drive hydraulic system pressure		6092 PSI
Tank capacities		
Hydraulic oil		19 US gal
Fuel tank		25 US gal
Noise and vibration		
Vibration on hands/arms		< 2.50 m/s ²
Miscellaneous		
Safety cab homologation		ROPS - FOPS cab (level 1)



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend