

# AL650

## ARTICULATED LOADERS



### Key Features

- ✓ 4-Post Canopy ROPS and FOPS certified
- ✓ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Differential Lock (Hydraulically Activated Front and Rear)
- ✓ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ✓ Lift Arm with Z-Bar Kinematics Return to Dig and Mechanical Self-Level
- ✓ Lift Arm Float Detent
- ✓ Hydraglide™ Ride Control\*
- ✓ High-Flow Auxiliary Hydraulics\*

\*Optional Features

### Key Specifications

- ✓ 6,409 lbs (2907 kg) Static Tipping Load with Bucket Straight
- ✓ 65 hp (48.5 kW) gross power @ 1560 rpm
- ✓ 8' 1" (2.47 m) height to top of ROPS
- ✓ 10' 3" (3.13 m) maximum lifting height (below forks)
- ✓ 10' 10" (3.31 m) outer turning radius

## SPECIFICATIONS

|                       |  | IMPERIAL   |
|-----------------------|--|--|
| Capacities            | Static tipping load with bucket (straight)                       | 6744 lb  |
|                       | Static tipping load with bucket (full turn)                      | 4916 lb  |
|                       | Static tipping load with forks (straight)                        | 5302 lb  |
|                       | Max. height of bucket pivot point                                | 10 ft 11 in  |
|                       | Max. lifting height (below forks)                                | 10 ft 3 in   |
| Weight and dimensions | Breakout force with bucket                                       | 5743 daN   |
|                       | Unladen weight (with forks) with 4-post canopy                   | 9149 lb  |
|                       | Wheelbase  | 79 in  |
|                       | Overall width of 4 posts canopy                                  | 4 ft 6 in  |
|                       | Overall cab width  | 4 ft 6 in  |
|                       | Overall height with 4 posts canopy                               | 8 ft 1 in  |
|                       | Overall height with cab  | 8 ft 1 in  |
|                       | Tilt-up angle  | 45 °   |
|                       | Tilt-down angle  | 45 °   |
|                       | External turning radius (over tyres)                             | 10 ft 10 in  |
|                       | Articulation angle   | 45 °   |
|                       | Overall width less bucket  | 5 ft 5 in  |
|                       | Overall length - Less Bucket                                     | 14 ft  |
| Ground clearance      | 1 ft 3 in  |  |
| Engine                | Engine brand   | Yanmar   |
|                       | Engine model   | 4TNV98CT   |
|                       | Engine norm  | Tier 4 final   |
|                       | Number of cylinders / Capacity of cylinders                      | 4 - 201 in³  |
|                       | I.C. Engine power rating / Power                                 | 64.40 Hp / 48 kW   |
|                       | Max. torque / Engine rotation                                    | 207 ft/lbs / 2300 rpm                                      |
| Engine cooling system | 2 radiators water + hydraulic oil                                |  |
| Transmission          | Transmission type  | Hydrostatic  |
|                       | Number of gears (forward / reverse)                              | 2 / 2  |
|                       | Max. travel speed (may vary according to applicable regulations) | 19 mph   |
|                       | Travel speed (laden)   | 19 mph   |
|                       | Differential lock  | Front and rear locking of the machine                      |
|                       | Parking brake  | Manual   |
|                       | Service brake  | Hydraulic disc brake on front axle, acting on all 4 wheels |
| Hydraulics            | Hydraulic pump type  | Gear pump  |
|                       | Hydraulic flow - Pressure  | 18 US gpm / 2901 PSI                                       |
|                       | High-Flow Option (l/min)   | 26 US gpm  |
|                       | Drive hydraulic system pressure                                  | 6092 PSI   |
| Tank capacities       | Hydraulic oil  | 19 US gal  |
|                       | Fuel tank  | 25 US gal  |
| Noise and vibration   | Vibration on hands/arms  | < 2.50 m/s²  |
| Miscellaneous         | Safety cab homologation  | ROPS - FOPS cab (level 1)                                  |



## STANDARD FEATURES

- Z-Bar Loader Linkage w/ Limited Self-Leveling
- Inching Pedal
- Lift Tilt Electronic Lockout Switch
- Adjustable and telescopic steering column
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Removable Rubber Floormat
- Tilt & Lift Arm Float Detent with Detent Disable
- Two-Speed Hydrostatic Drive System
- Power-A-Tach® Attachment Mounting System
- Reverse and Brake Tail Lights
- Differential Lock
- Articulation Locking Bar
- Front and Rear - Work Lights
- Canopy
- 12Volt Power Port
- Horn
- LED work lights on the boom (x2)

## OPTIONAL FEATURES

- Adaptive air suspension cloth-covered seat with heating and electric lumbar adjustment
- Back-Up Alarm
- Rotating Beacon
- Lockable Storage Box
- Engine Block Heater
- Canopy
- Speed control
- 12Volt Power Port
- Rear Auxiliary Hydraulics
- LED Work Lights
- Cabin with Heat
- Hydraglide™ Ride Control
- Strobe Light

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT