

# DL11-55 GEN:3

CONSTRUCTION TELEHANDLERS



## Key Features

- ✓ High capacity combined with high lift and great forward reach
- ✓ Simple F-N-R joystick operation
- ✓ Front outriggers standard
- ✓ Air tires standard

## Key Specifications

- ✓ 11,000 lbs. (4990 kg) maximum lift capacity
- ✓ 55' 5" (16.9 m) maximum lift height
- ✓ 5,500 lbs. (3629 kg) lift capacity to 55' 5" (16.9m)
- ✓ 120 hp (89 kW) Cummins diesel engine

## SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	11000 lb	4989.51 kg
	Max. lifting height	55 ft 5 in	16.89 m
	Maximum outreach	40 ft	12.20 m
Weight and dimensions	Length to face of forks	21 ft	6.40 m
	Overall width	8 ft 2 in	2.50 m
	Overall height	8 ft 6 in	2.60 m
	Wheelbase	10 ft 10 in	3.30 m
	Ground clearance	16 in	406 mm
	Overall cab width	2 ft 11 in	0.88 m
	External turning radius	12 ft 2 in	3.70 m
	Unladen weight	28459 lb	12909 kg
	Overall weight	28459 lb	12909 kg
	Standard tires	14 x 24	14 x 24
Engine	Frame leveling longitudinal +/-	10 °	10 °
	Engine brand	Cummins	Cummins
	Engine norm	Tier 4 final	Tier 4 final
	Engine model	QSF 3.8 Tier IV	QSF 3.8 Tier IV
	I.C. Engine power rating - Power	120 Hp / 89 kW	120 Hp / 89 kW
	Engine rotation	2500 rpm	2500 rpm
Transmission	Transmission type	Powershift	Powershift
	Number of gears (forward)	4	4
	Max. travel speed	23 mph	36.70 km/h
	Parking brake	Hydraulic spring release SAHR	Hydraulic spring release SAHR
	Service brake	Wet disc brakes	Wet disc brakes
	Axle Manufacturer	Dana	Dana
Hydraulics	Hydraulic pump type	Gear pump	Gear pump
	Hydraulic flow / Pressure	43 US gpm-3002 PSI	162.80 l/min-207 bar
Tank capacities	Hydraulic oil	41 US gal	155 l
	Fuel tank	30 US gal	114 l
Miscellaneous	Controls	Single Joystick FNR	Single Joystick FNR



## STANDARD FEATURES

- Rear Axle Stabilization
- Front Outriggers
- Back-Up Alarm
- Engine Block Heater
- Four Wheel Drive
- Self-Leveling Forks
- Battery Disconnect
- Single Joystick F-N-R (GEN3)
- Frame Leveling
- Parking Brake

## OPTIONAL FEATURES

- A/C Cabin
- Suspension Seat
- Boom Tip Lift Hook
- Light Package - LED
- Solid Rubber Tires
- Foam Filled Tires
- PWP System 3-Section Boom
- Cabin with Heat
- Rear camera with cab display screen
- Radio
- Easy Manager
- Cabin with Heat and Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT