

DL12-40 GEN:3

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ High capacity for industrial, mining energy and infrastructure applications
- ✓ Simple F-N-R joystick operation
- ✓ Compact 12' 2" turning radius
- ✓ Under 8' tall

Key Specifications

- ✓ 12,000 lbs. (5443 kg) maximum lift capacity
- ✓ 40' 4" (12.3 m) maximum lift height
- ✓ 10,000 lbs. (4536 kg) lift capacity to 40' 4" (12.3 m)
- ✓ 120 hp (89 kW) Cummins diesel engine

SPECIFICATIONS

		IMPERIAL	METRIC
Capacities	Max. capacity	12000 lb	5443.10 kg
	Max. lifting height	40 ft 4 in	12.29 m
	Maximum outreach	26 ft 3 in	8 m
Weight and dimensions	Length to face of forks	19 ft 4 in	5.90 m
	Overall width	8 ft 2 in	2.50 m
	Overall height	7 ft 11 in	2.41 m
	Wheelbase	10 ft 8 in	3.25 m
	Ground clearance	16 in	406 mm
	Overall cab width	34 in	876 mm
	External turning radius (over tyres)	12 ft 2 in	3.70 m
	Overall weight	25298 lb	11475 kg
	Standard tires	14 x 24	14 x 24
Engine	Frame leveling longitudinal +/-	10 °	10 °
	Engine brand	Cummins	Cummins
	Engine norm	Tier 4 final	Tier 4 final
	Engine model	QSF 3.8 Tier IV	QSF 3.8 Tier IV
	I.C. Engine power rating - Power	120 Hp / 89 kW	120 Hp / 89 kW
Transmission	Engine rotation	2500 rpm	2500 rpm
	Transmission type	Powershift	Powershift
	Max. travel speed	23 mph	36.70 km/h
	Parking brake	Hydraulic spring release SAHR	Hydraulic spring release SAHR
	Service brake	Wet disc brakes	Wet disc brakes
Hydraulics	Axle Manufacturer	Dana	Dana
	Hydraulic pump type	Gear pump	Gear pump
Tank capacities	Hydraulic flow / Pressure	43 US gpm-3002 PSI	162.80 l/min-207 bar
	Hydraulic oil	41 US gal	155 l
Miscellaneous	Fuel tank	30 US gal	114 l
	Controls	Single Joystick FNR	Single Joystick FNR



STANDARD FEATURES

- Rear Axle Stabilization
- Steering Column with Tilt & Extension Adjustments
- Back-Up Alarm
- Engine Block Heater
- Four Wheel Drive
- Self-Leveling Forks
- Battery Disconnect
- Single Joystick F-N-R (GEN3)
- Frame Leveling
- Parking Brake

OPTIONAL FEATURES

- A/C Cabin
- Suspension Seat
- Light Package - LED
- Solid Rubber Tires
- Front Outriggers
- Foam Filled Tires
- PWP System 3-Section Boom
- Cabin with Heat
- Rear camera with cab display screen
- Radio
- Easy Manager
- Cabin with Heat and Air Conditioning

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT