


Technical sheet :

# EP 15 EASY


---



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Metric                   |
|-------|---|-----------|--------------------------|
| 1.1   | Manufacturer  |           | MANITOU                  |
| 1.2   | Model Name  |           | EP 15 Easy               |
| 1.3   | Power source  |           | Electrical               |
| 1.4   | Operator type   |           | Pedestrian               |
| 1.5   | Max. capacity   | Q         | 1500 kg                  |
| 1.6   | Load center of gravity  | c         | 600 mm                   |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 960 mm                   |
| 1.9   | Wheelbase   | y         | 1285 mm                  |
|       | <b>Weight</b>   |           |                          |
| 2.1   | Service weight  |           | 189 kg                   |
|       | <b>Wheels</b>   |           |                          |
| 3.1   | Tires type  |           | Bandage                  |
| 3.2   | Dimensions of front wheels                                      |           | 210 x 70                 |
| 3.3   | Dimensions of rear wheels                                       |           | 80 x 64                  |
| 3.4   | Number of stabilizer wheels / Size of the stabilizer wheels     |           | 2 / 70x40                |
| 3.5.2 | Number of drive wheels / front wheels / rear wheels             |           | 1 / 2 / 4                |
| 3.6   | Front wheel gauge   | b10       | 404 mm                   |
| 3.7   | Rear wheel gauge  | b11       | 400 mm                   |
|       | <b>Dimensions</b>   |           |                          |
| 4.15  | Fork height in low position                                     | h13       | 80 mm                    |
| 4.19  | Overall length  | l1        | 1669 mm                  |
| 4.20  | Length to face of forks   | l2        | 485 mm                   |
| 4.21  | Overall width   | b1        | 568 mm                   |
| 4.22  | Forks section / width / length                                  | s / e / l | 50 mm x 160 mm x 1150 mm |
| 4.25  | Forks spread  | b5        | 560 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 30 mm                    |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 2142 mm                  |
| 4.35  | Turning radius (raised forks)                                   | Wa        | 1442 mm                  |
| 4.4   | Mast lifting height   | h3        | 120 mm                   |
| 4.9   | Height tiller min.  | h14       | 720 mm                   |
|       | <b>Performances</b>   |           |                          |
| 5.1   | Travel speed (laden / unladen)                                  |           | 4.50 km/h / 4.80 km/h    |
| 5.7   | Gradeability (laden / unladen)                                  |           | 6 % / 15 %               |
| 5.10  | Service brake   |           | Electro magnetic         |
| 5.11  | Parking brake   |           | Handle Release           |
|       | <b>Engine</b>   |           |                          |
| 6.1   | Drive motor rating S2 60 min                                    |           | 0.65 kW                  |
| 6.2   | Lift motor rating at S3 15%                                     |           | 0.80 kW                  |
| 6.3   | Battery according to DIN 43531/35/36 A, B, C                    |           | Lithium                  |
| 6.4   | Battery voltage / capacity                                      |           | 24 V / 40 Ah             |
| 6.5   | Battery weight (+/- 5%)   |           | 12 kg                    |
|       | <b>Miscellaneous</b>  |           |                          |
| 8.1   | Type of drive control   |           | AC                       |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 70 dB                  |

## EP 15 Easy - Dimensional drawing





**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes