Technical sheet :






	Technical characteristics	
1.1	Manufacturer	
1.2	Model Name	
1.3	Power source	
1.4	Operator type	
1.5	Max. capacity	Q
1.6	Load center of gravity	С
1.8	Load distance, centre of drive axle to fork	x
1.9	Wheelbase	у
	Weight	
2.1	Service weight	
	Wheels	
3.1	Tires type	
3.5.2	Number of drive wheels - Size of drive wheels	
3.3	Number of load wheels - Size of load wheels	
3.5	Number of front wheels / rear wheels	
3.6	Front wheel gauge	b10
3.7	Rear wheel gauge	b11
	Dimensions	
4.8	Seat height/stand height	h7
4.19	Overall length	1
4.20	Length to face of forks	12
4.21	Overall width	b1
4.22	Forks section / width / length	s / e / l
4.23	Fork carriage ISO 2328 (class/form) A/B	
4.26	Distance between wheel arms/loading surfaces	b4
4.25.1	Width over forks min. / max.	b5
4.32	Ground clearance at centre of wheelbase	m2
4.33	Aisle width for 1000 x 1200 pallet lengthways	
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast
4.35	Tuming radius	Wa
4.7	Height of overhead guard (cabin)	h6
	Performances	
5.1	Travel speed (laden / unladen)	
5.2	Lifting speed (laden / unladen)	
5.3	Lowering speed (laden / unladen)	
5.4.1	Reach speed (with load / without load)	
5.7	Gradeability (laden / unladen)	
5.10	Service brake	
	Engine	
6.1	Drive motor rating S2 60 min	
6.2	Lift motor rating at S3 15%	
6.3	Battery according to DIN 43531/35/36 A, B, C	
6.4	Battery voltage / capacity	
6.5	Battery weight (+/- 5%)	
0.0	Miscellaneous	
8.1	Type of drive control	
8.3	Oil flow rate for attachments	
8.4	Sound level at the driver's ear according to DIN 12 053	
0.4		

Metric
Manitou
ER 12
Electrical
Seated
1200 kg
600 mm
335 mm
1378 mm
2580 kg
Vulkollan
1 x 355 x 155
2 x 220 x 85
1/2
0 mm
995 mm
1077 mm
2413 mm
1263 mm
1120 mm
40 mm x 100 mm / 1150 mm 2A
2A 900 mm
316 mm / 697 mm
70 mm
2694 mm
2094 mm
1598 mm
2205 mm
12.30 km/h / 12.50 km/h
0.50 m/s / 0.65 m/s
0.58 m/s / 0.55 m/s
0.20 m/s / 0.20 m/s
7.50 % / 11.10 %
Electric
5.90 kW
11 kW
DIN43531 B
48 V / 310 Ah
730 kg
Electronic
25 l/min
57.40 dB

ER 12 - Dimensional drawing



Characteristics of masts and residual capacities

Free Lift Triplex (FLT)	FLT 48	FLT 54	FLT 57	FLT 63	FLT 68	
a - Mast/fork carriage tilt, forward	۰	3	3	3	3	3
β - Mast/fork carriage tilt, backward		1	1	1	1	1
h1 - Mast lowered height	mm	2140	2340	2440	2640	2790
h2 - Mast free lift	mm	1600	1800	1900	2100	2250
h3 - Mast lifting height	mm	4800	5400	5700	6300	6800
h4 - Mast extended height	mm	5380	5980	6280	6880	7330
Residual capacity with integrated side shift at max heigth	kg	1200	1200	1200	1000	700



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes