

Technical sheet :

ER 12



 **MANITOU**
HANDLING YOUR WORLD

Technical drawing of the 1000 Series 2-Door Refrigerator-Freezer, showing front, top, and side views with dimensions in millimeters.

Front View Dimensions:

- Overall Width: 611
- Overall Height: 1830
- Top Panel Width: 545
- Top Panel Height: 125
- Freezer Section Width: 545
- Freezer Section Height: 125
- Refrigerator Section Width: 545
- Refrigerator Section Height: 125
- Bottom Panel Width: 545
- Bottom Panel Height: 125
- Door Width: 545
- Door Height: 125
- Internal Width: 545
- Internal Height: 125
- Internal Width (Refrigerator): 545
- Internal Height (Refrigerator): 125
- Internal Width (Freezer): 545
- Internal Height (Freezer): 125

Top View Dimensions:

- Overall Width: 611
- Overall Depth: 611
- Top Panel Width: 545
- Top Panel Depth: 125
- Freezer Section Width: 545
- Freezer Section Depth: 125
- Refrigerator Section Width: 545
- Refrigerator Section Depth: 125
- Bottom Panel Width: 545
- Bottom Panel Depth: 125
- Door Width: 545
- Door Depth: 125
- Internal Width: 545
- Internal Depth: 125
- Internal Width (Refrigerator): 545
- Internal Depth (Refrigerator): 125
- Internal Width (Freezer): 545
- Internal Depth (Freezer): 125

Side View Dimensions:

- Overall Width: 611
- Overall Depth: 611
- Top Panel Width: 545
- Top Panel Depth: 125
- Freezer Section Width: 545
- Freezer Section Depth: 125
- Refrigerator Section Width: 545
- Refrigerator Section Depth: 125
- Bottom Panel Width: 545
- Bottom Panel Depth: 125
- Door Width: 545
- Door Depth: 125
- Internal Width: 545
- Internal Depth: 125
- Internal Width (Refrigerator): 545
- Internal Depth (Refrigerator): 125
- Internal Width (Freezer): 545
- Internal Depth (Freezer): 125

Characteristics of masts and residual capacities

Free Lift Triplex (FLT)		FLT 48	FLT 54	FLT 57	FLT 63	FLT 68
α - Mast/fork carriage tilt, forward	°	3	3	3	3	3
β - Mast/fork carriage tilt, backward	°	1	1	1	1	1
h1 - Mast lowered height	mm	2140	2340	2440	2640	2790
h2 - Mast free lift	mm	1600	1800	1900	2100	2250
h3 - Mast lifting height	mm	4800	5400	5700	6300	6800
h4 - Mast extended height	mm	5380	5980	6280	6880	7330
Residual capacity with integrated side shift at max heigh	kg	1200	1200	1200	1000	700

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes