Technical sheet :






	Technical characteristics
1.1	Manufacturer
1.2	Model Name
1.3	Power source
1.4	Operator type
1.5	Max. capacity
1.6	Load center of gravity
1.8	Load distance, centre of drive axle to fork
.9	Wheelbase
	Weight
2.1	Service weight
	Wheels
.1	Tires type
5.2	Number of drive wheels - Size of drive wheels
.3	Number of load wheels - Size of load wheels
5	Number of front wheels / rear wheels
6	Front wheel gauge
.7	Rear wheel gauge
	Dimensions
4.7	Height of overhead guard (cabin)
.8	Seat height/stand height
19	Overall length
0	Length to face of forks
21	Overall width
2	Forks section / width / length
23	Fork carriage ISO 2328 (class/form) A/B
26	Distance between wheel arms/loading surfaces
5.1	Width over forks min. / max.
32	Ground clearance at centre of wheelbase
3	Aisle width for 1000 x 1200 pallet lengthways
34	Aisle width for 800 x 1200 pallet lengthways
5	Turning radius
	Performances
	Travel speed (laden / unladen)
2	Lifting speed (laden / unladen)
3	Lowering speed (laden / unladen)
1	Reach speed (with load / without load)
.7	Gradeability (laden / unladen)
0	Service brake
	Engine
1	Drive motor rating S2 60 min
2	Lift motor rating at S3 15%
3	Battery according to DIN 43531/35/36 A, B, C
4	Battery voltage / capacity
5	Battery weight (+/- 5%)
	Miscellaneous
8.1	Type of drive control
.3	Oil flow rate for attachments
4	Sound level at the driver's ear according to DIN 12 053
	······································

	Metric
	Manitou
	ER 12
	Electrical
	Seated
2	1200 kg
)	600 mm
(307 mm
/	1378 mm
	2580 kg
	Vulkollan
	1 x 355 x 155
	2 x 220*85
	1/2
10	0 mm
11	995 mm
6	2205 mm
7	1077 mm
1	2413 mm
2	1263 mm
1	1120 mm
e/l	40 mm x 100 mm / 1150 mm
	2A
4	900 mm
5	316 mm / 697 mm
12	70 mm
	2701 mm
st /a	2768 mm 1598 mm
la	1398 11111
	12.30 km/h / 12.50 km/h
	0.46 m/s / 0.54 m/s
	0.58 m/s / 0.60 m/s
	0.20 m/s / 0.20 m/s
	7.50 % / 11.10 %
	Electric
	5.90 kW
	11 kW
	DIN43531 B
	48 V / 420 Ah
	730 kg
	Electronic
	25 l/min
	57.40 dB

ER 12 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 32	FVD 36	FVD 38	FVD 42	FVD 45	FVD 48
Mast/fork carriage tilt, forward	۰	4	4	4	4	4	4
Mast/fork carriage tilt, backward	۰	1	1	1	1	1	1
h1 - Mast lowered height	mm	2170	2370	2470	2670	2820	2970
h2 - Mast free lift	mm	125	125	125	125	125	125
h3 - Mast lifting height	mm	3200	3600	3800	4200	4500	4800
h4 - Mast extended height	mm	3780	4180	4380	4780	5080	5380
Residual capacity with integrated side shift at max heigth	kg	1200	1200	1200	1200	1200	1200

Free Lift Triplex (FLT)		FLT 48	FLT 54	FLT 57	FLT 63	FLT 68
Mast/fork carriage tilt, forward	۰	3	3	3	3	3
Mast/fork carriage tilt, backward	٥	1	1	1	1	1
h1 - Mast lowered height	mm	2140	2340	2440	2640	2790
h2 - Mast free lift	mm	1600	1800	1900	2100	2250
h3 - Mast lifting height	mm	4800	5400	5700	6300	6800
h4 - Mast extended height	mm	5380	5980	6280	6880	7330
Residual capacity with integrated side shift at max heigth	kg	1200	1200	1200	1000	700



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes