

Technical sheet :

# ER 12



 **MANITOU**  
HANDLING YOUR WORLD

Technical drawing of the 1000 Series 2-Door Refrigerator-Freezer, showing front and side views with dimensions.

**Front View Dimensions:**

- Overall Width: B
- Overall Height: h1
- Top Panel Width: b1
- Top Panel Height: h2
- Top Panel Depth: b2
- Top Panel Thickness: t1
- Top Panel Material: Wp
- Top Panel Color: RAL 9005
- Top Panel Finish: Glossy
- Top Panel Texture: Smooth
- Top Panel Shape: Rectangular
- Top Panel Position: Top
- Top Panel Orientation: Horizontal
- Top Panel Function: Door
- Top Panel Material: Steel
- Top Panel Color: Black
- Top Panel Finish: Glossy
- Top Panel Texture: Smooth
- Top Panel Shape: Rectangular
- Top Panel Position: Top
- Top Panel Orientation: Horizontal
- Top Panel Function: Door

**Side View Dimensions:**

- Overall Width: B
- Overall Height: h1
- Top Panel Width: b1
- Top Panel Height: h2
- Top Panel Depth: b2
- Top Panel Thickness: t1
- Top Panel Material: Wp
- Top Panel Color: RAL 9005
- Top Panel Finish: Glossy
- Top Panel Texture: Smooth
- Top Panel Shape: Rectangular
- Top Panel Position: Top
- Top Panel Orientation: Horizontal
- Top Panel Function: Door
- Top Panel Material: Steel
- Top Panel Color: Black
- Top Panel Finish: Glossy
- Top Panel Texture: Smooth
- Top Panel Shape: Rectangular
- Top Panel Position: Top
- Top Panel Orientation: Horizontal
- Top Panel Function: Door

# Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 32	FVD 36	FVD 38	FVD 42	FVD 45	FVD 48
Mast/fork carriage tilt, forward	°	4	4	4	4	4	4
Mast/fork carriage tilt, backward	°	1	1	1	1	1	1
h1 - Mast lowered height	mm	2170	2370	2470	2670	2820	2970
h2 - Mast free lift	mm	125	125	125	125	125	125
h3 - Mast lifting height	mm	3200	3600	3800	4200	4500	4800
h4 - Mast extended height	mm	3780	4180	4380	4780	5080	5380
Residual capacity with integrated side shift at max height	kg	1200	1200	1200	1200	1200	1200

Free Lift Triplex (FLT)		FLT 48	FLT 54	FLT 57	FLT 63	FLT 68
Mast/fork carriage tilt, forward	°	3	3	3	3	3
Mast/fork carriage tilt, backward	°	1	1	1	1	1
h1 - Mast lowered height	mm	2140	2340	2440	2640	2790
h2 - Mast free lift	mm	1600	1800	1900	2100	2250
h3 - Mast lifting height	mm	4800	5400	5700	6300	6800
h4 - Mast extended height	mm	5380	5980	6280	6880	7330
Residual capacity with integrated side shift at max height	kg	1200	1200	1200	1000	700

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes