

Technical sheet :

ER 20



 **MANITOU**
HANDLING YOUR WORLD

The top view (left) shows the vehicle's footprint with dimensions: overall width B , wheelbase $b1$, front overhang $b4$, rear overhang $b5$, and track width $b6$. The side view (right) shows the vehicle's profile with dimensions: overall height H , front overhang $h1$, wheelbase $h2$, rear overhang $h3$, and ground clearance $h4$. Other side view dimensions include $h5$, $h6$, $h7$, $h8$, $h9$, $h10$, $h11$, $h12$, $h13$, $h14$, $h15$, $h16$, $h17$, $h18$, $h19$, $h20$, $h21$, $h22$, $h23$, $h24$, $h25$, $h26$, $h27$, $h28$, $h29$, $h30$, $h31$, $h32$, $h33$, $h34$, $h35$, $h36$, $h37$, $h38$, $h39$, $h40$, $h41$, $h42$, $h43$, $h44$, $h45$, $h46$, $h47$, $h48$, $h49$, $h50$, $h51$, $h52$, $h53$, $h54$, $h55$, $h56$, $h57$, $h58$, $h59$, $h60$, $h61$, $h62$, $h63$, $h64$, $h65$, $h66$, $h67$, $h68$, $h69$, $h70$, $h71$, $h72$, $h73$, $h74$, $h75$, $h76$, $h77$, $h78$, $h79$, $h80$, $h81$, $h82$, $h83$, $h84$, $h85$, $h86$, $h87$, $h88$, $h89$, $h90$, $h91$, $h92$, $h93$, $h94$, $h95$, $h96$, $h97$, $h98$, $h99$, $h100$, $h101$, $h102$, $h103$, $h104$, $h105$, $h106$, $h107$, $h108$, $h109$, $h110$, $h111$, $h112$, $h113$, $h114$, $h115$, $h116$, $h117$, $h118$, $h119$, $h120$, $h121$, $h122$, $h123$, $h124$, $h125$, $h126$, $h127$, $h128$, $h129$, $h130$, $h131$, $h132$, $h133$, $h134$, $h135$, $h136$, $h137$, $h138$, $h139$, $h140$, $h141$, $h142$, $h143$, $h144$, $h145$, $h146$, $h147$, $h148$, $h149$, $h150$, $h151$, $h152$, $h153$, $h154$, $h155$, $h156$, $h157$, $h158$, $h159$, $h160$, $h161$, $h162$, $h163$, $h164$, $h165$, $h166$, $h167$, $h168$, $h169$, $h170$, $h171$, $h172$, $h173$, $h174$, $h175$, $h176$, $h177$, $h178$, $h179$, $h180$, $h181$, $h182$, $h183$, $h184$, $h185$, $h186$, $h187$, $h188$, $h189$, $h190$, $h191$, $h192$, $h193$, $h194$, $h195$, $h196$, $h197$, $h198$, $h199$, $h200$, $h201$, $h202$, $h203$, $h204$, $h205$, $h206$, $h207$, $h208$, $h209$, $h210$, $h211$, $h212$, $h213$, $h214$, $h215$, $h216$, $h217$, $h218$, $h219$, $h220$, $h221$, $h222$, $h223$, $h224$, $h225$, $h226$, $h227$, $h228$, $h229$, $h230$, $h231$, $h232$, $h233$, $h234$, $h235$, $h236$, $h237$, $h238$, $h239$, $h240$, $h241$, $h242$, $h243$, $h244$, $h245$, $h246$, $h247$, $h248$, $h249$, $h250$, $h251$, $h252$, $h253$, $h254$, $h255$, $h256$, $h257$, $h258$, $h259$, $h260$, $h261$, $h262$, $h263$, $h264$, $h265$, $h266$, $h267$, $h268$, $h269$, $h270$, $h271$, $h272$, $h273$, $h274$, $h275$, $h276$, $h277$, $h278$, $h279$, $h280$, $h281$, $h282$, $h283$, $h284$, $h285$, $h286$, $h287$, $h288$, $h289$, $h290$, $h291$, $h292$, $h293$, $h294$, $h295$, $h296$, $h297$, $h298$, $h299$, $h300$, $h301$, $h302$, $h303$, $h304$, $h305$, $h306$, $h307$, $h308$, $h309$, $h310$, $h311$, $h312$, $h313$, $h314$, $h315$, $h316$, $h317$, $h318$, $h319$, $h320$, $h321$, $h322$, $h323$, $h324$, $h325$, $h326$, $h327$, $h328$, $h329$, $h330$, $h331$, $h332$, $h333$, $h334$, $h335$, $h336$, $h337$, $h338$, $h339$, $h340$, $h341$, $h342$, $h343$, $h344$, $h345$, $h346$, $h347$, $h348$, $h349$, $h350$, $h351$, $h352$, $h353$, $h354$, $h355$, $h356$, $h357$, $h358$, $h359$, $h360$, $h361$, $h362$, $h363$, $h364$, $h365$, $h366$, $h367$, $h368$, $h369$, $h370$, $h371$, $h372$, $h373$, $h374$, $h375$, $h376$, $h377$, $h378$, $h379$, $h380$, $h381$, $h382$, $h383$, $h384$, $h385$, $h386$, $h387$, $h388$, $h389$, $h390$, $h391$, $h392$, $h393$, $h394$, $h395$, $h396$, $h397$, $h398$, $h399$, $h400$, $h401$, $h402$, $h403$, $h404$, $h405$, $h406$, $h407$, $h408$

Characteristics of masts and residual capacities

Free Lift Triplex (FLT)		FLT 48	FLT 54	FLT 57	FLT 63	FLT 68	FLT 73	FLT 80	FLT 85	FLT 90
Mast/fork carriage tilt, forward	°	3	3	3	3	3	3	3	3	3
Mast/fork carriage tilt, backward	°	1	1	1	1	1	1	1	1	1
h1 - Mast lowered height	mm	2140	2340	2640	2790	2957	3040	3190	3357	3523
h2 - Mast free lift	mm	16001	1800	1900	2100	2250	2400	2650	2800	2980
h3 - Mast lifting height	mm	4800	5400	5700	6300	6750	7250	7950	8450	8950
h4 - Mast extended height	mm	5380	5980	6880	7330	7830	8080	8530	9030	9530
Residual capacity with integrated side shift at max heigh	kg	2000	2000	2000	1850	1600				

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes