

Technical sheet :

# ES 414

---



The top view (left) shows the pallet truck from above. Dimensions include:  $b_1$  (total width),  $b_{10}$  (width of the handle assembly),  $b_{11}$  (width of the forks),  $b_5$  (width of the fork tips),  $l_2$  (distance from handle to fork base),  $l$  (total length),  $A_{st}$  (total length including handle),  $e$  (fork spacing), and  $W_a$  (width of the wheel assembly).

The side view (right) shows the pallet truck from the side. Dimensions include:  $h_{14}$  (height of the handle),  $h_1$  (height of the fork base),  $h_2$  (height of the fork base to the wheel),  $h_3$  (height of the fork base to the wheel),  $h_4$  (height of the fork base to the wheel),  $c$  (distance from handle to wheel),  $\rho$  (radius of the wheel),  $m_1$  (width of the wheel),  $s$  (width of the wheel),  $x$  (distance from handle to wheel),  $y$  (distance from handle to wheel),  $l_1$  (total length), and  $h_{13}$  (height of the wheel).

## Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 29	FVD 34	FVD 38
h1 - Mast lowered height	mm	1940	2190	2390
h3 - Mast lifting height	mm	2940	3440	3840
h4 - Mast extended height	mm	3365	3865	4265
Residual capacity at max height	kg	1250	1050	850
Height at max capacity	mm	2700	2700	2700

Free Lift Duplex (FLD)		FLD 29	FLD 34
h1 - Mast lowered height	mm	1940	2190
h2 - Mast free lift	mm	1420	1670
h3 - Mast lifting height	mm	2935	3435
h4 - Mast extended height	mm	3365	3865
Residual capacity at max height	kg	1250	1000
Height at max capacity	mm	2700	2700

Free Lift Triplex (FLT)		FLT 42
h1 - Mast lowered height	mm	1890
h2 - Mast free lift	mm	1380
h3 - Mast lifting height	mm	4240
h4 - Mast extended height	mm	4678
Residual capacity at max height	kg	700
Height at max capacity	mm	2700



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes