

Technical sheet :


ES 720



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer	Manitou	
1.2	Model Name	ES 720	
1.3	Power source	Electrical - Lead	
1.4	Operator type	Pedestrian	
1.5	Max. capacity	2000 kg	
1.6	Load center of gravity	600 mm	
1.8	Distance from Load backrest to center of rear axle	665 mm	
1.9	Wheelbase	1104 mm	
Weight			
2.1	Service weight	1420 kg	
Wheels			
3.1	Tires type	Polyurethane cushion	
3.3	Number of load wheels / Size of load wheels	2 / 125 x 50	
3.4	Number of castor wheels	1	
3.5	Number of stabilizer wheels / Size of the stabilizer wheels	2 / 254 x 50	
3.6	Number of front wheels / rear wheels	3 / 4	
3.5.2	Number of drive wheels / Size of drive wheels	1/254 x 50	
3.6	Front wheel gauge	878 mm	
3.7	Rear wheel gauge	395 mm	
Dimensions			
4.15	Fork height in low position	90 mm	
4.19	Overall length	1911 mm	
4.20	Length to face of forks	761 mm	
4.21	Overall width	1080 mm	
4.22	Forks section / width / length	70 mm / 185 mm / 1150 mm	
4.24	Fork carriage width	752 mm	
4.31	Ground clearance below mast	30 mm	
4.32	Ground clearance at centre of wheelbase	30 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	2335 mm	
4.34	Aisle Width for pallets 800 x 1200 crossways	2336 mm	
4.35	Turning radius	1468 mm	
4.9	Height tiller min. / max.	1030 mm / 1490 mm	
Performances			
5.1	Travel speed (laden / unladen)	6 km/h / 6 km/h	
5.2	Lifting speed (laden / unladen)	0.11 m/s / 0.20 m/s	
5.3	Lowering speed (laden / unladen)	0.22 m/s / 0.21 m/s	
5.8	Max Gradeability (laden / unladen)	5 % / 8 %	
5.10	Service brake	Electro magnetic	
Engine			
6.1	Drive motor rating S2 60 min	2 kW	
6.2	Lift motor rating at S3 15%	4 kW	
6.3	Battery according to DIN 43531/35/36 A, B, C	DIN 43535-B	
6.4	Battery voltage / capacity	24 V / 250 Ah	
6.5	Battery weight (+/- 5%)	250 kg	
Miscellaneous			
8.1	Type of drive control	AC	
8.4	Sound level at the driver's ear according to DIN 12 053	70 dB	

ES 720 - Dimensional drawing



Characteristics of masts and residual capacities

Central Cylinder Simplex (CCS)	CCS 15	CCS 17
h1 - Mast lowered height mm	1945	2195
h2 - Mast free lift mm	1420	1670
h3 - Mast lifting height mm	1500	1700
h4 - Mast extended height mm	1965	2215
Residual capacity at max height kg	2000	2000
Height at max capacity mm	1510	1760

Full Visibility Duplex (FVD)	FVD 29	FVD 34	FVD 38
h1 - Mast lowered height mm	1945	2195	2395
h3 - Mast lifting height mm	2900	3400	3800
h4 - Mast extended height mm	3400	3900	4300
Residual capacity at max height kg	2000	1800	1600
Height at max capacity mm	2940	2900	2900

Free Lift Duplex (FLD)	FLD 29	FLD 34
h1 - Mast lowered height mm	1945	2195
h2 - Mast free lift mm	1420	1670
h3 - Mast lifting height mm	2900	3400
h4 - Mast extended height mm	3400	3900
Residual capacity at max height kg	2000	1700
Height at max capacity mm	2930	2900

Free Lift Triplex (FLT)	FLT 42	FLT 47	FLT 54
h1 - Mast lowered height mm	1900	2065	2305
h2 - Mast free lift mm	1380	1540	1790
h3 - Mast lifting height mm	4200	4700	5400
h4 - Mast extended height mm	4720	5200	5930
Residual capacity at max height kg	1300	1000	700
Height at max capacity mm	2900	2900	2900



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes