

Technical sheet :

# ES 720



| Technical characteristics |   | Metric    |                          |
|---------------------------|---|-----------|--------------------------|
| 1.1                       | Manufacturer  |           | Manitou                  |
| 1.2                       | Model Name  |           | ES 720                   |
| 1.3                       | Power source  |           | Electrical - Lead        |
| 1.4                       | Operator type   |           | Pedestrian               |
| 1.5                       | Max. capacity   | Q         | 2000 kg                  |
| 1.6                       | Load center of gravity                                      | c         | 600 mm                   |
| 1.8                       | Distance from Load backrest to center of rear axle          | x         | 665 mm                   |
| 1.9                       | Wheelbase   | y         | 1104 mm                  |
| Weight                    |   |           |                          |
| 2.1                       | Service weight  |           | 1420 kg                  |
| Wheels                    |   |           |                          |
| 3.1                       | Tires type  |           | Polyurethane cushion     |
| 3.3                       | Number of load wheels / Size of load wheels                 |           | 2 / 125 x 50             |
| 3.4                       | Number of castor wheels                                     |           | 1                        |
| 3.4                       | Number of stabilizer wheels / Size of the stabilizer wheels |           | 2 / 254 x 50             |
| 3.5                       | Number of front wheels / rear wheels                        |           | 3 / 4                    |
| 3.5.2                     | Number of drive wheels / Size of drive wheels               |           | 1/254 x 50               |
| 3.6                       | Front wheel gauge   | b10       | 878 mm                   |
| 3.7                       | Rear wheel gauge  | b11       | 395 mm                   |
| Dimensions                |   |           |                          |
| 4.15                      | Fork height in low position                                 | h13       | 90 mm                    |
| 4.19                      | Overall length  | l1        | 1911 mm                  |
| 4.20                      | Length to face of forks                                     | l2        | 761 mm                   |
| 4.21                      | Overall width   | b1        | 1080 mm                  |
| 4.22                      | Forks section / width / length                              | s / e / l | 70 mm / 185 mm / 1150 mm |
| 4.24                      | Fork carriage width   | b3        | 752 mm                   |
| 4.31                      | Ground clearance below mast                                 | m1        | 30 mm                    |
| 4.32                      | Ground clearance at centre of wheelbase                     | m2        | 30 mm                    |
| 4.33                      | Aisle Width for pallets 1000 x 1200 crossways               | Ast       | 2335 mm                  |
| 4.34                      | Aisle Width for pallets 800 x 1200 crossways                | Ast       | 2336 mm                  |
| 4.35                      | Turning radius  | Wa        | 1468 mm                  |
| 4.9                       | Height tiller min. / max.                                   | h14       | 1030 mm / 1490 mm        |
| Performances              |   |           |                          |
| 5.1                       | Travel speed (laden / unladen)                              |           | 6 km/h / 6 km/h          |
| 5.2                       | Lifting speed (laden / unladen)                             |           | 0.11 m/s / 0.20 m/s      |
| 5.3                       | Lowering speed (laden / unladen)                            |           | 0.22 m/s / 0.21 m/s      |
| 5.8                       | Max Gradeability (laden / unladen)                          |           | 5 % / 8 %                |
| 5.10                      | Service brake   |           | Electro magnetic         |
| Engine                    |   |           |                          |
| 6.1                       | Drive motor rating S2 60 min                                |           | 2 kW                     |
| 6.2                       | Lift motor rating at S3 15%                                 |           | 4 kW                     |
| 6.3                       | Battery according to DIN 43531/35/36 A, B, C                |           | DIN 43535-B              |
| 6.4                       | Battery voltage / capacity                                  |           | 24 V / 250 Ah            |
| 6.5                       | Battery weight (+/- 5%)                                     |           | 250 kg                   |
| Miscellaneous             |   |           |                          |
| 8.1                       | Type of drive control                                       |           | AC                       |
| 8.4                       | Sound level at the driver's ear according to DIN 12 053     |           | 70 dB                    |

ES 720 - Dimensional drawing



## Characteristics of masts and residual capacities

| Central Cylinder Simplex (CCS)  |    | CCS 15 | CCS 17 |
|---------------------------------|----|--------|--------|
| h1 - Mast lowered height        | mm | 1945   | 2195   |
| h2 - Mast free lift             | mm | 1420   | 1670   |
| h3 - Mast lifting height        | mm | 1500   | 1700   |
| h4 - Mast extended height       | mm | 1965   | 2215   |
| Residual capacity at max height | kg | 2000   | 2000   |

| Full Visibility Duplex (FVD)    |    | FVD 29 | FVD 34 | FVD 38 |
|---------------------------------|----|--------|--------|--------|
| h1 - Mast lowered height        | mm | 1945   | 2195   | 2395   |
| h3 - Mast lifting height        | mm | 2900   | 3400   | 3800   |
| h4 - Mast extended height       | mm | 3400   | 3900   | 4300   |
| Residual capacity at max height | kg | 2000   | 1800   | 1600   |
| Height at max capacity          | mm | 2940   | 2900   | 2900   |

| Free Lift Duplex (FLD)          |    | FLD 29 | FLD 34 |
|---------------------------------|----|--------|--------|
| h1 - Mast lowered height        | mm | 1945   | 2195   |
| h2 - Mast free lift             | mm | 1420   | 1670   |
| h3 - Mast lifting height        | mm | 2900   | 3400   |
| h4 - Mast extended height       | mm | 3400   | 3900   |
| Residual capacity at max height | kg | 2000   | 1700   |
| Height at max capacity          | mm | 2930   | 2900   |

| Free Lift Triplex (FLT)         |    | FLT 42 | FLT 47 | FLT 54 |
|---------------------------------|----|--------|--------|--------|
| h1 - Mast lowered height        | mm | 1900   | 2065   | 2305   |
| h2 - Mast free lift             | mm | 1380   | 1540   | 1790   |
| h3 - Mast lifting height        | mm | 4200   | 4700   | 5400   |
| h4 - Mast extended height       | mm | 4720   | 5200   | 5930   |
| Residual capacity at max height | kg | 1300   | 1000   | 700    |
| Height at max capacity          | mm | 2900   | 2900   | 2900   |

**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes