

Technical sheet :

# ES 725

---



| Technical characteristics |   |           | Metric                   |
|---------------------------|---|-----------|--------------------------|
| 1.1                       | Manufacturer  |           | Manitou                  |
| 1.2                       | Model Name  |           | ES 725                   |
| 1.3                       | Power source  |           | Electrical               |
| 1.4                       | Operator type   |           | Pedestrian               |
| 1.5                       | Max. capacity   | Q         | 2500 kg                  |
| 1.6                       | Load center of gravity                                      | c         | 600 mm                   |
| 1.8                       | Distance from Load backrest to center of rear axle          | x         | 655 mm                   |
| 1.9                       | Wheelbase   | y         | 1156 mm                  |
| Weight                    |   |           |                          |
| 2.1                       | Service weight  |           | 1280 kg                  |
| Wheels                    |   |           |                          |
| 3.1                       | Tires type  |           | Polyurethane             |
| 3.3                       | Number of load wheels / Size of load wheels                 |           | 2 / 78x78                |
| 3.4                       | Number of castor wheels                                     |           | 1                        |
| 3.4                       | Number of stabilizer wheels / Size of the stabilizer wheels |           | 2 / 150x50               |
| 3.5                       | Number of front wheels / rear wheels                        |           | 2 / 4                    |
| 3.5.2                     | Number of drive wheels / Size of drive wheels               |           | 1/320x110                |
| 3.6                       | Front wheel gauge   | b10       | 844 mm                   |
| 3.7                       | Rear wheel gauge  | b11       | 370 mm                   |
| Dimensions                |   |           |                          |
| 4.15                      | Fork height in low position                                 | h13       | 90 mm                    |
| 4.19                      | Overall length  | l1        | 1915 mm                  |
| 4.20                      | Length to face of forks                                     | l2        | 765 mm                   |
| 4.21                      | Overall width   | b1        | 974 mm                   |
| 4.22                      | Forks section / width / length                              | s / e / l | 70 mm / 210 mm / 1150 mm |
| 4.24                      | Fork carriage width   | b3        | 840 mm                   |
| 4.31                      | Ground clearance below mast                                 | m1        | 30 mm                    |
| 4.32                      | Ground clearance at centre of wheelbase                     | m2        | 30 mm                    |
| 4.35                      | Turning radius  | Wa        | 1472 mm                  |
| 4.9                       | Height tiller min. / max.                                   | h14 / h14 | 900 mm / 1400 mm         |
| Performances              |   |           |                          |
| 5.1                       | Travel speed (laden / unladen)                              |           | 4.90 km/h / 6 km/h       |
| 5.2                       | Lifting speed (laden / unladen)                             |           | 0.08 m/s / 0.15 m/s      |
| 5.3                       | Lowering speed (laden / unladen)                            |           | 0.15 m/s / 0.11 m/s      |
| 5.8                       | Max Gradeability (laden / unladen)                          |           | 4 % / 7 %                |
| 5.10                      | Service brake   |           | Electro magnetic         |
| Engine                    |   |           |                          |
| 6.1                       | Drive motor rating S2 60 min                                |           | 1.20 kW                  |
| 6.2                       | Lift motor rating at S3 15%                                 |           | 3 kW                     |
| 6.3                       | Battery according to DIN 43531/35/36 A, B, C                |           | Traction                 |
| 6.4                       | Battery voltage / capacity                                  |           | 24 V / 189 Ah            |
| 6.5                       | Battery weight (+/- 5%)                                     |           | 190 kg                   |
| Miscellaneous             |   |           |                          |
| 8.1                       | Type of drive control                                       |           | DC                       |
| 8.4                       | Sound level at the driver's ear according to DIN 12 053     |           | 65 dB                    |

ES 725 - Dimensional drawing



## Characteristics of masts and residual capacities

| Visibilité totale Simplex (FVS) |    | FVS 14 |
|---------------------------------|----|--------|
| h1 - Mast lowered height        | mm | 1930   |
| h2 - Mast free lift             | mm | 1490   |
| h3 - Mast lifting height        | mm | 1490   |
| h4 - Mast extended height       | mm | 1930   |
| Residual capacity at max height | kg | 2500   |
| Height at max capacity          | mm | 1490   |

| Full Visibility Duplex (FVD)    |    | FVD 27 |
|---------------------------------|----|--------|
| h1 - Mast lowered height        | mm | 1900   |
| h2 - Mast free lift             | mm | 77     |
| h3 - Mast lifting height        | mm | 2700   |
| h4 - Mast extended height       | mm | 3240   |
| Residual capacity at max height | kg | 2500   |
| Height at max capacity          | mm | 2760   |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes