

Technical sheet :

# ES 820 LI



 **MANITOU**  
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer		Manitou
1.2	Model Name		ES 820 LI
1.3	Power source		Electrical - Lead
1.4	Operator type		Pedestrian
1.5	Max. capacity	Q	2000 kg
1.51	Nominal capacity on wrapover forks	Q	2000 kg
1.6	Load center of gravity	c	600 mm
1.8	Distance from Load backrest to center of rear axle	x	716 mm
1.9	Wheelbase	y	1509 mm
Weight			
2.1	Service weight		1800 kg
2.2	Weight on front axle (laden) / rear axle (laden)		1360 kg / 2500 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1250 kg / 550 kg
Wheels			
3.1	Tires type		Polyurethane cushion
3.3	Number of load wheels / Size of load wheels		4 / 82 x 68
3.4	Number of castor wheels		1
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		2 / 120 x 50
3.5	Number of front wheels / rear wheels		3 / 4
3.5.2	Number of drive wheels / Size of drive wheels		1/254x100
3.6	Front wheel gauge	b10	664 mm
3.7	Rear wheel gauge	b11	375 mm
Dimensions			
4.15	Fork height in low position	h13	86 mm
4.19	Overall length	l1	2123 mm
4.20	Length to face of forks	l2	973 mm
4.21	Overall width	b1	890 mm
4.22	Forks section / width / length	s / e / l	70 mm / 200 mm / 1150 mm
4.24	Fork carriage width	b3	700 mm
4.31	Ground clearance below mast	m1	20 mm
4.32	Ground clearance at centre of wheelbase	m2	21 mm
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	2572 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2531 mm
4.6	Initial lift	h5	110 mm
4.35	Turning radius	Wa	1719 mm
4.9	Height tiller min. / max.	h14	900 mm / 1400 mm
Performances			
5.1	Travel speed (laden / unladen)		6 km/h / 6 km/h
5.2	Lifting speed (laden / unladen)		0.11 m/s / 0.20 m/s
5.3	Lowering speed (laden / unladen)		0.21 m/s / 0.22 m/s
5.8	Max Gradeability (laden / unladen)		6 % / 10 %
5.10	Service brake		Electro magnetic
Engine			
6.1	Drive motor rating S2 60 min		2 kW
6.2	Lift motor rating at S3 15%		4 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Traction
6.4	Battery voltage / capacity		24 V / 315 Ah
6.5	Battery weight (+/- 5%)		273 kg
Miscellaneous			
8.1	Type of drive control		DC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB

ES 820 LI - Dimensional drawing



## Characteristics of masts and residual capacities

Central Cylinder Simplex (CCS)		CCS 15	CCS 17
h1 - Mast lowered height	mm	1957	2207
h3 - Mast lifting height	mm	1500	1700
h4 - Mast extended height	mm	1963	2213
Residual capacity at max height	kg	2000	2000

  

Full Visibility Duplex (FVD)		FVD 29	FVD 34	FVD 38
h1 - Mast lowered height	mm	1957	2207	2407
h3 - Mast lifting height	mm	2900	3400	3800
h4 - Mast extended height	mm	3393	3893	4293
Residual capacity at max height	kg	1950	1600	1300

  

Free Lift Duplex (FLD)		FLD 29	FLD 34
h1 - Mast lowered height	mm	1957	2207
h2 - Mast free lift	mm	1507	1757
h3 - Mast lifting height	mm	2900	3400
h4 - Mast extended height	mm	3388	3888
Residual capacity at max height	kg	1900	1550

  

Free Lift Triplex (FLT)		FLT 42	FLT 47	FLT 54
h1 - Mast lowered height	mm	1915	2075	2315
h2 - Mast free lift	mm	1472	1632	1882
h3 - Mast lifting height	mm	4200	4700	5400
h4 - Mast extended height	mm	4713	5193	5923
Residual capacity at max height	kg	950	750	500



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes