

Technical sheet :


ES 820 LI



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric	
1.1	Manufacturer	Manitou	
1.2	Model Name	ES 820 LI	
1.3	Power source	Electrical - Lead	
1.4	Operator type	Pedestrian	
1.5	Max. capacity	2000 kg	
1.51	Nominal capacity on wrapover forks	2000 kg	
1.6	Load center of gravity	600 mm	
1.8	Distance from Load backrest to center of rear axle	716 mm	
1.9	Wheelbase	1509 mm	
Weight			
2.1	Service weight	1800 kg	
2.2	Weight on front axle (laden) / rear axle (laden)	1360 kg / 2500 kg	
2.3	Weight on front axle (Unladen) / rear axle (Unladen)	1250 kg / 550 kg	
Wheels			
3.1	Tires type	Polyurethane cushion	
3.3	Number of load wheels / Size of load wheels	4 / 82 x 68	
3.4	Number of castor wheels	1	
3.4	Number of stabilizer wheels / Size of the stabilizer wheels	2 / 120 x 50	
3.5	Number of front wheels / rear wheels	3 / 4	
3.5.2	Number of drive wheels / Size of drive wheels	1/254x100	
3.6	Front wheel gauge	664 mm	
3.7	Rear wheel gauge	375 mm	
Dimensions			
4.15	Fork height in low position	86 mm	
4.19	Overall length	2123 mm	
4.20	Length to face of forks	973 mm	
4.21	Overall width	890 mm	
4.22	Forks section / width / length	70 mm / 200 mm / 1150 mm	
4.24	Fork carriage width	700 mm	
4.31	Ground clearance below mast	20 mm	
4.32	Ground clearance at centre of wheelbase	21 mm	
4.33	Aisle Width for pallets 1000 x 1200 crossways	2572 mm	
4.34	Aisle width for 800 x 1200 pallet lengthways	2531 mm	
4.6	Initial lift	110 mm	
4.35	Turning radius	1719 mm	
4.9	Height tiller min. / max.	900 mm / 1400 mm	
Performances			
5.1	Travel speed (laden / unladen)	6 km/h / 6 km/h	
5.2	Lifting speed (laden / unladen)	0.11 m/s / 0.20 m/s	
5.3	Lowering speed (laden / unladen)	0.21 m/s / 0.22 m/s	
5.8	Max Gradeability (laden / unladen)	6 % / 10 %	
5.10	Service brake	Electro magnetic	
Engine			
6.1	Drive motor rating S2 60 min	2 kW	
6.2	Lift motor rating at S3 15%	4 kW	
6.3	Battery according to DIN 43531/35/36 A, B, C	Traction	
6.4	Battery voltage / capacity	24 V / 315 Ah	
6.5	Battery weight (+/- 5%)	273 kg	
Miscellaneous			
8.1	Type of drive control	DC	
8.4	Sound level at the driver's ear according to DIN 12 053	65 dB	

ES 820 LI - Dimensional drawing



Characteristics of masts and residual capacities

Central Cylinder Simplex (CCS)	CCS 15	CCS 17
h1 - Mast lowered height mm	1955	2205
h2 - Mast free lift mm	1510	1760
h3 - Mast lifting height mm	1510	1760
h4 - Mast extended height mm	1965	2215
Residual capacity at max height kg	2000	2000

Full Visibility Duplex (FVD)	FVD 29	FVD 34
h1 - Mast lowered height mm	1955	2205
h3 - Mast lifting height mm	2940	3440
h4 - Mast extended height mm	3400	3900
Residual capacity at max height kg	1600	1300

Free Lift Duplex (FLD)	FLD 29	FLD 34
h1 - Mast lowered height mm	2205	2205
h2 - Mast free lift mm	1510	1760
h3 - Mast lifting height mm	2935	3435
h4 - Mast extended height mm	3895	3895
Residual capacity at max height kg	1600	1300

Free Lift Triplex (FLT)	FLT 42	FLT 47	FLT 54
h1 - Mast lowered height mm	1915	2075	2315
h2 - Mast free lift mm	1470	1630	1880
h3 - Mast lifting height mm	4250	4730	5460
h4 - Mast extended height mm	4725	5205	5895
Residual capacity at max height kg	750	550	450



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes