Technical sheet:

# **MBL-X 920 92P 5T2**

Manitou is committed to bringing value to its backhoe loaders by incorporating advanced and robust features for multi-application capabilities. MBL X 920 is powered by Tier -II/III engine. The structure of MBL X 920 is durable and designed for intensive operations. It comes with the latest cabin design and unbreakable bonnet which promises to deliver higher up-time and require low maintenance, even after prolonged usage. Customers get quick returns on their investments on top of an optimum Total Cost of Ownership. It comes with an option of features such as AC, multipurpose bucket.





Capacities	Metric		
Wheelbase 2 wheels drive	2185 mm		
Wheelbase 4 wheels drive	2130 mm		
Weight and dimensions			
Jnladen weight	7620 kg		
Jnladen weight with 4 WD	7620 kg		
Unladen weight with 4 WD 7 in 1	7908 kg		
Unladen weight 4WD - Side shift	7620 kg		
Overall length	I1 7330 mm		
Overall width	b1 2330 mm		
Overall width with stabilizers extended - Center mount only	3910 mm		
Cabin height	h6 2830 mm		
Height of cab with air conditioning (option)	h6** 2860 mm		
Overall height	h17 3790 mm		
-	Wa1 3850 mm		
External turning radius over tyres (braked)	Wa1 4200 mm		
External turning radius over tyres (unbraked)			
External turning radius over bucket (braked)	Wa5 5550 mm		
External turning radius over bucket (unbraked)	Wa5 5700 mm	00.1000	
Standard tires front / rear	12.5 x 18 - 12 PR / 16.9		
Optional tires (front / rear)	9 x 16 - 16 PR / 14 x 2	25 - 20 PR	
Ground clearance	m4 280 mm		
Performances			
Travel speed forward 1st / 2nd	5.40 km/h / 8.60		
Travel speed forward 3rd / 4th	19.90 km/h / 40 l	.cm/h	
Engine			
Engine brand	Perkins		
Engine model	1104C 44T Turbo Charged Wa	1104C 44T Turbo Charged Water Cooled Tier-I	
Displacement	4.40		
Engine power (kW) / Gross Power	68.50 kW @ 2200	) rpm	
Max. torque	395 Nm		
Battery voltage / capacity	12 V / 75 Ah	ı	
Transmission			
Transmission brand	Carraro		
Number of gears (forward / reverse)	4 / 4	4 / 4	
Torque converter stall ratio	3.01:1		
Service brake	Wet disc brake	Wet disc brakes	
Hydraulics			
Hydraulic flow	142 l/min		
Main relief pressure	225 bar		
Tank capacities			
Hydraulic oil	901		
Liquid cooling tank volume	16		
Fuel	145 I		
Transmission oil	17.50 I		
Engine oil	9.10		
Dil rear axle	17.50		
Bucket	17.301		
Backhoe standard capacity	0.24 m³		
Width backhoe bucket	0.24 III <sup>o</sup> 892 mm		
Loader standard capacity		1 m³	
Width loader bucket	2235 mm		
Miscellaneous			
Power steering	Yes		
Front steer axle of oscillation 2WD	20 °		
Steering wheels (front / rear)	2/2		

### Performance backhoe

p1 - Max dig depth (mm)
r1 - Max reach ground level to slew center (mm)
r2 - Max loading reach (mm)
Max operating height (mm)
Max loading height (mm)
p2 - Max straight wall dig depth (mm)
a10 - Max bucket rotation (°)
Total side shift (mm)
Dipper tearout (kgF)
Bucket tearout (kgF)
Hydraulic lift capacity (kg)


Standard dipper	
4741	
5730	
1996	
5626	
3871	
2602	
194	
1198	
4336	
5810	
1460	


## Performance loader


Max dump angle (°)
h26 - Max operating height (loader version) (mm)
h23 - Max dump height at 45° (mm)
h24 - Max loadover height (mm)
h25 - Max hinge pin height (mm)
r3 - Max reach at full height 45° (mm)
p3 - Below ground dig depth (mm)
a13 - Rollback at ground (°)
Shovel breakout (kgf)
Arms breakout (kgF)
Lifting capacity at full height (kg)

Standard shovel
51
4230
2780
3310
3570
710
156
45
5229
5312
3819

## MBL-X 920 92P ST2 - Dimensional drawing











#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes