

Technical sheet :

# MC-X 18-2

---



|       | Technical characteristics                               |           | Metric                   |
|-------|---|-----------|--------------------------|
| 1.1   | Manufacturer  |           | Manitou                  |
| 1.2   | Model Name  |           | MC-X 18-2                |
| 1.3   | Power source  |           | Diesel                   |
| 1.4   | Operator type   |           | Seated                   |
| 1.5   | Max. capacity   | Q         | 1800 kg                  |
| 1.6   | Load center of gravity                                  | c         | 500 mm                   |
| 1.8   | Load distance, centre of drive axle to fork             | x         | 616 mm                   |
| 1.9   | Wheelbase   | y         | 1900 mm                  |
|       | <b>Weight</b>   |           |                          |
| 2.1   | Service weight  |           | 3405 kg                  |
| 2.2   | Weight on front axle (laden) / rear axle (laden)        |           | 4200 kg / 1005 kg        |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)    |           | 1625 kg / 1780 kg        |
|       | <b>Wheels</b>   |           |                          |
| 3.1   | Tires type  |           | Pneumatic                |
| 3.2   | Dimensions of front wheels                              |           | 12.5/80 - 18/12 SL R4    |
| 3.3   | Dimensions of rear wheels                               |           | 7.00-12/12 ED PLUS       |
| 3.5   | Number of front wheels / rear wheels                    |           | 2 / 2                    |
| 3.5.2 | Number of drive wheels                                  |           | 2                        |
| 3.6   | Front wheel gauge                                       | b10       | 1159 mm                  |
| 3.7   | Rear wheel gauge  | b11       | 1112 mm                  |
|       | <b>Dimensions</b>                                       |           |                          |
| 4.7   | Overall height of low overhead guard (Buggy version)    | h6*       | 1990 mm                  |
| 4.8   | Seat height/stand height                                | h7        | 1034 mm                  |
| 4.19  | Overall length  | l1        | 4100 mm                  |
| 4.20  | Length to face of forks                                 | l2        | 2950 mm                  |
| 4.21  | Overall width   | b1        | 1450 mm                  |
| 4.22  | Forks section x width x length                          | s / e / l | 35 mm x 100 mm / 1150 mm |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                 |           | 2A                       |
| 4.24  | Fork carriage width                                     | b3        | 1260 mm                  |
| 4.31  | Ground clearance below mast                             | m1        | 300 mm                   |
| 4.32  | Ground clearance at centre of wheelbase                 | m2        | 320 mm                   |
| 4.35  | Turning radius  | Wa        | 2585 mm                  |
|       | <b>Performances</b>                                     |           |                          |
| 5.1   | Travel speed (laden / unladen)                          |           | 12 km/h / 24.90 km/h     |
| 5.2   | Lifting speed (laden / unladen)                         |           | 0.40 m/s / 0.40 m/s      |
| 5.3   | Lowering speed (laden / unladen)                        |           | 0.40 m/s / 0.40 m/s      |
| 5.5   | Drawbar pull (Laden / Unladen)                          |           | 1050 daN / 1100 daN      |
| 5.7   | Gradeability (laden / unladen)                          |           | 21 % / 34 %              |
| 5.10  | Service brake   |           | Hydraulic                |
|       | <b>Engine</b>   |           |                          |
| 7.2   | Engine power according to ISO 1585                      |           | 27 kW                    |
| 7.1   | Engine brand / model                                    |           | Kubota / V1505           |
| 7.2   | Engine power according to ISO 1585                      |           | 27 kW                    |
| 7.3   | Rated speed   |           | 3000 rpm                 |
| 7.4   | Number of cylinders / Capacity of cylinders             |           | 4 - 1498 cm³             |
|       | <b>Miscellaneous</b>                                    |           |                          |
| 8.1   | Type of drive control                                   |           | Cable                    |
| 8.2   | Working hydraulic pressure for attachments              |           | 180 bar                  |
| 8.3   | Oil flow rate for attachments                           |           | 37 l/min                 |
| 8.4   | Sound level at the driver's ear according to DIN 12 053 |           | 79 dB                    |

## MC-X 18-2 - Dimensional drawing



## Characteristics of masts and residual capacities

| Full Visibility Duplex (FVD)      |    | FVD 33 | FVD 37 | FVD 40 | FVD 45 |
|-----------------------------------|----|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward  | °  | 10     | 10     | 10     | 10     |
| Mast/fork carriage tilt, backward | °  | 12     | 12     | 12     | 12     |
| h1 - Mast lowered height          | mm | 2348   | 2608   | 2798   | 3048   |
| h2 - Mast free lift               | mm | 85     | 85     | 85     | 85     |
| h3 - Mast lifting height          | mm | 3300   | 3700   | 4000   | 4500   |
| h4 - Mast extended height         | mm | 4018   | 4428   | 4768   | 5268   |
| Residual capacity at max height   | kg | 1800   |        |        |        |
| Height at max capacity            | mm | 3300   | 2500   | 2500   | 2500   |

| Free Lift Triplex (FLT)           |    | FLT 37 | FLT 43 | FLT 47 | FLT 55  |
|-----------------------------------|----|--------|--------|--------|---------|
| Mast/fork carriage tilt, forward  | °  | 10     | 10     | 10     | 6       |
| Mast/fork carriage tilt, backward | °  | 12     | 12     | 12     | 6       |
| h1 - Mast lowered height          | mm | 1998   | 2198   | 2348   | 2608000 |
| h2 - Mast free lift               | mm | 1305   | 1505   | 1655   | 1915    |
| h3 - Mast lifting height          | mm | 3700   | 4300   | 4700   | 5500    |
| h4 - Mast extended height         | mm | 4453   | 5053   | 5453   | 6253    |
| Height at max capacity            | mm | 2500   | 2500   | 2500   | 2500    |

| Full Visibility Triplex (FVT)     |    | FVT 33 |
|-----------------------------------|----|--------|
| Mast/fork carriage tilt, forward  | °  | 10     |
| Mast/fork carriage tilt, backward | °  | 12     |
| h1 - Mast lowered height          | mm | 1888   |
| h2 - Mast free lift               | mm | 135    |
| h3 - Mast lifting height          | mm | 3300   |
| h4 - Mast extended height         | mm | 4048   |
| Height at max capacity            | mm | 2500   |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes