

Ficha técnica :

MC-X 18-2



The image contains two technical drawings of a forklift. The left drawing is a top-down view showing the forklift's footprint. It includes dimensions for the overall width ($b1$), the width of the mast ($b3$), the width of the body ($b10$), the width of the rear section ($b11$), and the distance between the mast arms (e). A dimension of 100 is shown at the bottom left. The right drawing is a side profile view showing the forklift's height and length. It includes dimensions for the mast height ($h1$), the height of the body ($h2$), the height of the rear section ($h3$), the height of the mast at the top ($h4$), the height of the rear section at the back ($h6$), the height of the rear section at the front ($h7$), the height of the rear section at the side ($h10$), the height of the mast at the side ($h11$), the height of the mast at the front ($h12$), the height of the mast at the rear ($h13$), the height of the mast at the side ($h14$), the height of the mast at the front ($h15$), the height of the mast at the rear ($h16$), the height of the mast at the side ($h17$), the height of the mast at the front ($h18$), the height of the mast at the rear ($h19$), the height of the mast at the side ($h20$), the height of the mast at the front ($h21$), the height of the mast at the rear ($h22$), the height of the mast at the side ($h23$), the height of the mast at the front ($h24$), the height of the mast at the rear ($h25$), the height of the mast at the side ($h26$), the height of the mast at the front ($h27$), the height of the mast at the rear ($h28$), the height of the mast at the side ($h29$), the height of the mast at the front ($h30$), the height of the mast at the rear ($h31$), the height of the mast at the side ($h32$), the height of the mast at the front ($h33$), the height of the mast at the rear ($h34$), the height of the mast at the side ($h35$), the height of the mast at the front ($h36$), the height of the mast at the rear ($h37$), the height of the mast at the side ($h38$), the height of the mast at the front ($h39$), the height of the mast at the rear ($h40$), the height of the mast at the side ($h41$), the height of the mast at the front ($h42$), the height of the mast at the rear ($h43$), the height of the mast at the side ($h44$), the height of the mast at the front ($h45$), the height of the mast at the rear ($h46$), the height of the mast at the side ($h47$), the height of the mast at the front ($h48$), the height of the mast at the rear ($h49$), the height of the mast at the side ($h50$), the height of the mast at the front ($h51$), the height of the mast at the rear ($h52$), the height of the mast at the side ($h53$), the height of the mast at the front ($h54$), the height of the mast at the rear ($h55$), the height of the mast at the side ($h56$), the height of the mast at the front ($h57$), the height of the mast at the rear ($h58$), the height of the mast at the side ($h59$), the height of the mast at the front ($h60$), the height of the mast at the rear ($h61$), the height of the mast at the side ($h62$), the height of the mast at the front ($h63$), the height of the mast at the rear ($h64$), the height of the mast at the side ($h65$), the height of the mast at the front ($h66$), the height of the mast at the rear ($h67$), the height of the mast at the side ($h68$), the height of the mast at the front ($h69$), the height of the mast at the rear ($h70$), the height of the mast at the side ($h71$), the height of the mast at the front ($h72$), the height of the mast at the rear ($h73$), the height of the mast at the side ($h74$), the height of the mast at the front ($h75$), the height of the mast at the rear ($h76$), the height of the mast at the side ($h77$), the height of the mast at the front ($h78$), the height of the mast at the rear ($h79$), the height of the mast at the side ($h80$), the height of the mast at the front ($h81$), the height of the mast at the rear ($h82$), the height of the mast at the side ($h83$), the height of the mast at the front ($h84$), the height of the mast at the rear ($h85$), the height of the mast at the side ($h86$), the height of the mast at the front ($h87$), the height of the mast at the rear ($h88$), the height of the mast at the side ($h89$), the height of the mast at the front ($h90$), the height of the mast at the rear ($h91$), the height of the mast at the side ($h92$), the height of the mast at the front ($h93$), the height of the mast at the rear ($h94$), the height of the mast at the side ($h95$), the height of the mast at the front ($h96$), the height of the mast at the rear ($h97$), the height of the mast at the side ($h98$), the height of the mast at the front ($h99$), the height of the mast at the rear ($h100$).

Características de los mástiles y capacidad residual

Full Visibility Duplex (FVD)		FVD 33	FVD 37	FVD 40	FVD 45
Mast/fork carriage tilt, forward	°	10	10	10	10
Mast/fork carriage tilt, backward	°	12	12	12	12
h1 - Mast lowered height	mm	2348	2608	2798	3048
h2 - Mast free lift	mm	85	85	85	85
h3 - Mast lifting height	mm	3300	3700	4000	4500
h4 - Mast extended height	mm	4018	4428	4768	5268
Residual capacity at max height	kg	1800			
Height at max capacity	mm	3300	2500	2500	2500

Free Lift Triplex (FLT)		FLT 37	FLT 43	FLT 47	FLT 55
Mast/fork carriage tilt, forward	°	10	10	10	6
Mast/fork carriage tilt, backward	°	12	12	12	6
h1 - Mast lowered height	mm	1998	2198	2348	2608000
h2 - Mast free lift	mm	1305	1505	1655	1915
h3 - Mast lifting height	mm	3700	4300	4700	5500
h4 - Mast extended height	mm	4453	5053	5453	6253
Height at max capacity	mm	2500	2500	2500	2500

Full Visibility Triplex (FVT)		FVT 33
Mast/fork carriage tilt, forward	°	10
Mast/fork carriage tilt, backward	°	12
h1 - Mast lowered height	mm	1888
h2 - Mast free lift	mm	135
h3 - Mast lifting height	mm	3300
h4 - Mast extended height	mm	4048
Height at max capacity	mm	2500



Oficina Central

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes