Technical sheet :








	Technical characteristics
1.1	Manufacturer
1.2	Model Name
1.3	Power source
1.4	Operator type
1.5	Max. capacity
1.6	Load center of gravity
1.8	Load distance, centre of drive axle to fork
1.9	Wheelbase
	Weight
2.1	Service weight
2.2	Weight on front axle (laden) / rear axle (laden)
2.3	Weight on front axle (Unladen) / rear axle (Unladen)
	Wheels
3.1	Tires type
3.2	Dimensions of front wheels
3.3	Dimensions of rear wheels
3.5	Number of front wheels / rear wheels
3.5.2	Number of drive wheels
3.6	Front wheel gauge
3.7	Rear wheel gauge
	Dimensions
4.7	Height of overhead guard (cabin) / Overall height of low overhead guard (Buggie version)
4.8	Seat height/stand height
4.19	Overall length
4.20	Length to face of forks
4.21	Overall width
4.22	Forks section x width x length
4.23	Fork carriage ISO 2328 (class/form) A/B
4.24	Fork carriage width
4.31	Ground clearance below mast
4.32	Ground clearance at centre of wheelbase
4.35	Turning radius
	Performances
5.1	Travel speed (laden / unladen)
5.2	Lifting speed (laden / unladen)
5.3	Lowering speed (laden / unladen)
5.10	Service brake
	Engine
7.2	Engine power according to ISO 1585
7.1	Engine brand / model
7.2	Engine power according to ISO 1585
7.3	Rated speed
7.4	Number of cylinders / Capacity of cylinders
	Miscellaneous
8.1	Type of drive control
8.2	Working hydraulic pressure for attachments
8.3	Oil flow rate for attachments
8.4	Sound level at the driver's ear according to DIN 12 053

MC-X 25-2	Created on 3 May 2024 at 11:39:37 AM UTC
	Metric
	Manitou
	MC-X 25-2
	Diesel
	Seated
Q	2500 kg
С	500 mm
x	621 mm
у	1900 mm
	3875 kg
	5510 kg / 865 kg
	1533 kg / 2342 kg
	Pneumatic
	12,5/80-18/12 SL R4
	7.00-12/12 ED PLUS
	2 / 2
	2
b10	1159 mm
b11	1112 mm
h6 / h6*	2155 mm / 1990 mm
h7	1034 mm
1	4195 mm
12	3045 mm
b1	1450 mm
s / e / l	40 mm x 122 mm / 1150 mm
	2A
b3	1260 mm
m1	300 mm
m2	320 mm
Wa	2620 mm
	12 km/h / 24.90 km/h
	0.47 m/s / 0.46 m/s
	0.50 m/s / 0.30 m/s
	Hydraulic brakes by loss of pressure
	36 kW
	Kubota / V2403
	36 kW
	2700 rpm
	4 - 2434 cm ³
	Cable
	180 bar
	53 l/min
	82 dB

MC-X 25-2 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 33	FVD 37	FVD 45
Mast/fork carriage tilt, forward	٥	10	10	10
Mast/fork carriage tilt, backward	٥	12	12	12
h1 - Mast lowered height	mm	2338	2598	3038
h2 - Mast free lift	mm	112	112	112
h3 - Mast lifting height	mm	3300	3700	4500
h4 - Mast extended height	mm	4090	4490	5290
Height at max capacity	mm	2500	2500	2500

Free Lift Triplex (FLT)		FLT 34	FLT 37	FLT 40	FLT 43	FLT 47	FLT 55
Mast/fork carriage tilt, forward	٥	10	10	10	10	10	б
Mast/fork carriage tilt, backward	٥	12	12	12	12	12	6
h1 - Mast lowered height	mm	1988	2088	2188	2338	2438	2788
h2 - Mast free lift	mm	1210	1310	1410	1510	1660	1920
h3 - Mast lifting height	mm	3400	3700	4000	4300	4700	5500
h4 - Mast extended height	mm	4236	4536	4836	5168	5536	6408
Height at max capacity	mm	2500	2500	2500	2500	2500	2500

Full Visibility Triplex (FVT)		FVT 33
Mast/fork carriage tilt, forward	۰	10
Mast/fork carriage tilt, backward	٥	12
h1 - Mast lowered height	mm	1878
h2 - Mast free lift	mm	124
h3 - Mast lifting height	mm	3300
h4 - Mast extended height	mm	4079
Height at max capacity	mm	2500



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes