

Technical sheet :




MHT 10160 ST5



 **MANITOU**
HANDLING YOUR WORLD


| Capacities | | Imperial |
|---|-----------|--|
| Max. capacity | | 35274 lb |
| Load center of gravity | c | 24 in |
| Max. lifting height | | 31 ft 6 in |
| Maximum outreach | | 17 ft 1 in |
| Weight and dimensions | | |
| Overall length | l1 | 24 ft 1 in |
| Unladen weight (with forks) | | 45658 lb |
| Ground clearance | m4 | 1 ft 5 in |
| Wheelbase | y | 11 ft 1 in |
| Length to face of forks | l2 | 20 ft 2 in |
| Overall width | b1 | 8 ft 2 in |
| Overall height | h17 | 9 ft 10 in |
| Overall cab width | b4 | 3 ft 1 in |
| Tilt-up angle | a4 | 12 ° |
| Tilt-down angle | a5 | 104 ° |
| External turning radius (over tyres) | Wa1 | 17 ft 1 in |
| Forks length / width / section | l / e / s | 47 in x 7 in x 3 in |
| Frame leveling corrector | a9 | 9 ° |
| Wheels | | |
| Standard tires | | 17,5-R25 |
| Number of front wheels / rear wheels | | 2 / 2 |
| Drive wheels (front / rear) | | 2 / 2 |
| Steering mode | | 2 wheel steer, 4 wheel steer, Crab mode |
| Engine | | |
| Engine brand | | Yanmar |
| Engine norm | | Stage V, Tier 4 |
| Engine model | | 4TN107FTT-6SMU1 |
| Number of cylinders / Capacity of cylinders | | 4 - 279 in³ |
| Engine power (Hp / kW) | | 173 Hp / 127 kW |
| Max. torque / Engine rotation | | 594 ft/lbs@1500 rpm |
| Engine cooling system | | Water |
| Number of batteries | | 2 |
| Battery voltage | | 12 V |
| Drawbar pull | | 11770 daN |
| Transmission | | |
| Transmission type | | Hydrostatic |
| Number of gears (forward / reverse) | | 2 / 2 |
| Max. travel speed | | 19 mph |
| Parking brake | | Automatic negative parking brake |
| Service brake | | Oil-immersed multi-discs braking on front & rear axles |
| Gradeability (laden / unladen) | | 32.40 % / 55.40 % |
| Hydraulics | | |
| Hydraulic pump type | | Variable displacement pump |
| Hydraulic flow - Pressure | | 45 US gpm - 5076 PSI |
| Tank capacities | | |
| Engine oil | | 3 US gal |
| Hydraulic oil | | 77 US gal |
| Fuel | | 83 US gal |
| Diesel Exhaust fluid (AdBlue® type) | | 6 US gal |
| Noise and vibration | | |
| Noise to environment (LwA) | | 108 dB |
| Vibration on hands/arms | | 8 ft/s² |
| Miscellaneous | | |
| Cab certification | | Cabin ROPS - FOPS level 2 |
| Controls | | JSM |
| Attachment recognition system (E-Reco) | | Standard |

MHT 10160 ST5 - Dimensional drawing




MHT 10160 ST5 - Load chart


Machine on tires with forks LC 600 mm (Imperial)




Machine on tires with forks LC 1200 mm Imperial




Machine on tires with 3-hook jib 16000 kg (Imperial)




Machine on tires with platform Imperial



Machine on tires with tire handler TH 51 (Imperial)



Machine on tires with cylinder handler CH 4 (Imperial)





Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes