

Ficha técnica :

MI-X 25 G



 **MANITOU**
HANDLING YOUR WORLD

| Technical characteristics | | | Métrico |
|---------------------------|---|-----------|--------------------------|
| 1.1 | Manufacturer | | MANITOU |
| 1.2 | Model Name | | MI-X 25 G |
| 1.3 | Power source | | Lpg |
| 1.4 | Operator type | | Seated |
| 1.5 | Max. capacity | Q | 2500 kg |
| 1.6 | Load center of gravity | c | 500 mm |
| 1.8 | Load distance, centre of drive axle to fork | x | 465 mm |
| 1.9 | Wheelbase | y | 1600 mm |
| Weight | | | |
| 2.1 | Service weight | | 3895 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 5665 kg / 730 kg |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 1665 kg / 2230 kg |
| Wheels | | | |
| 3.1 | Tires type | | Inflatable |
| 3.2 | Dimensions of front wheels | | 7.00-12 12 |
| 3.3 | Dimensions of rear wheels | | 6.00-9 10 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 965 mm |
| 3.7 | Rear wheel gauge | b11 | 973 mm |
| Dimensions | | | |
| 4.7 | Height of overhead guard (cabin) | h6 | 2115 mm |
| 4.8 | Seat height/stand height | h7 | 1190 mm |
| 4.12 | Height of towing bar (coupling height) | h10 | 360 mm |
| 4.19 | Overall length | l1 | 3685 mm |
| 4.20 | Length to face of forks | l2 | 2535 mm |
| 4.21 | Overall width | b1 | 1155 mm |
| 4.21 | Overall width - Single wheels | b1 | 1155 mm |
| 4.22 | Forks section / width / length | s / e / l | 40 mm x 122 mm x 1150 mm |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | 2A |
| 4.24 | Fork carriage width | b3 | 1038 mm |
| 4.31 | Ground clearance below mast | m1 | 115 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 175 mm |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 3930 mm |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 4130 mm |
| 4.35 | Turning radius | Wa | 2265 mm |
| 4.36 | Internal turning radius (over tyres) | b13 | 145 mm |
| Performances | | | |
| 5.1 | Travel speed (laden / unladen) | | 19.40 km/h-19.70 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 0.47 m/s-0.55 m/s |
| 5.3 | Lowering speed (laden / unladen) | | 0.50 m/s-0.50 m/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 1700 daN / 1040 daN |
| 5.7 | Gradeability (laden / unladen) | | 20 % / 20 % |
| 5.10 | Service brake | | Hydraulic |
| Engine | | | |
| 7.1 | Engine brand / model | | GCT (ex-Nissan) / K25 |
| 7.2 | I.C. Engine power rating | | 35 kW |
| 7.3 | Rated speed | | 2400 rpm |
| 7.4 | Number of cylinders / Capacity of cylinders | | 4 - 2488 cm³ |
| | Energy consumption according to VDI cycle (Gas) | | 6.30 kg CO2/h |
| Miscellaneous | | | |
| 8.2 | Working hydraulic pressure for attachments | | 160 bar |
| 8.3 | Oil flow rate for attachments | | 72 l/min |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 80 dB |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | 80 dB |

MI-X 25 G - Diagrama dimensional





 **MANITOU**
HANDLING YOUR WORLD

Oficina Central

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes