

Scheda tecnica :

# MI 30 GST5



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                                       |           | Metico                     |
|-------|-----------------------------------------------------------------|-----------|----------------------------|
| 1.1   | Manufacturer                                                    |           | MANITOU                    |
| 1.2   | Model Name                                                      |           | MI 30 G ST5                |
| 1.3   | Power source                                                    |           | Lpg                        |
| 1.4   | Operator type                                                   |           | Seated                     |
| 1.5   | Max. capacity                                                   | Q         | 3000 kg                    |
| 1.6   | Load center of gravity                                          | c         | 500 mm                     |
| 1.8   | Load distance, centre of drive axle to fork                     | x         | 480 mm                     |
| 1.9   | Wheelbase                                                       | y         | 1700 mm                    |
|       | <b>Weight</b>                                                   |           |                            |
| 2.1   | Service weight                                                  |           | 4490 kg                    |
| 2.2   | Weight on front axle (laden) / rear axle (laden)                |           | 6560 kg / 930 kg           |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 1805 kg / 2685 kg          |
|       | <b>Wheels</b>                                                   |           |                            |
| 3.1   | Tires type                                                      |           | Super Elastic              |
| 3.2   | Dimensions of front wheels                                      |           | 28-9-15 12                 |
| 3.3   | Dimensions of rear wheels                                       |           | 6.50-10 10                 |
| 3.5   | Number of front wheels / rear wheels                            |           | 2 / 2                      |
| 3.5.2 | Number of drive wheels                                          |           | 2                          |
| 3.6   | Front wheel gauge                                               | b10       | 1005 mm                    |
| 3.7   | Rear wheel gauge                                                | b11       | 975 mm                     |
|       | <b>Dimensions</b>                                               |           |                            |
| 4.7   | Height of overhead guard (cabin)                                | h6        | 2130 mm                    |
| 4.8   | Seat height/stand height                                        | h7        | 1215 mm                    |
| 4.12  | Height of towing bar (coupling height)                          | h10       | 355 mm                     |
| 4.19  | Overall length                                                  | l1        | 3865 mm                    |
| 4.20  | Length to face of forks                                         | l2        | 2715 mm                    |
| 4.21  | Overall width                                                   | b1        | 1225 mm                    |
| 4.21  | Overall width - Single wheels                                   | b1        | 1225 mm                    |
| 4.21  | Overall width - Twinned wheels                                  | b1        | 1725 mm                    |
| 4.22  | Forks section / width / length                                  | s / e / l | 45 mm x 122 mm x 1150 mm   |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                         |           | 3A                         |
| 4.24  | Fork carriage width                                             | b3        | 1100 mm                    |
| 4.31  | Ground clearance below mast                                     | m1        | 130 mm                     |
| 4.32  | Ground clearance at centre of wheelbase                         | m2        | 200 mm                     |
| 4.33  | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 4140 mm                    |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4340 mm                    |
| 4.35  | Turning radius                                                  | Wa        | 2460 mm                    |
| 4.36  | Internal turning radius (over tyres)                            | b13       | 160 mm                     |
|       | <b>Performances</b>                                             |           |                            |
| 5.1   | Travel speed (laden / unladen)                                  |           | 20 km/h-20 km/h            |
| 5.2   | Lifting speed (laden / unladen)                                 |           | 0.50 m/s-0.53 m/s          |
| 5.3   | Lowering speed (laden / unladen)                                |           | 0.48 m/s-0.50 m/s          |
| 5.5   | Drawbar pull (Laden / Unladen)                                  |           | 2000 daN / 1080 daN        |
| 5.7   | Gradeability (laden / unladen)                                  |           | 20 % / 20 %                |
| 5.10  | Service brake                                                   |           | Hydraulic                  |
|       | <b>Engine</b>                                                   |           |                            |
| 7.1   | Engine brand / model                                            |           | GCT (ex-Nissan) / GK25 LPG |
| 7.2   | Engine power according to ISO 1585                              |           | 43.40 kW                   |
| 7.3   | Rated speed                                                     |           | 2700 rpm                   |
| 7.4   | Number of cylinders / Capacity of cylinders                     |           | 4 - 2488 cm³               |
|       | <b>Miscellaneous</b>                                            |           |                            |
| 8.2   | Working hydraulic pressure for attachments                      |           | 160 bar                    |
| 8.3   | Oil flow rate for attachments                                   |           | 35 l/min                   |
| 8.4   | Measured/guaranteed mean noise level at the ear of the operator |           | < 80 dB                    |

## MI 30 G ST5 - Disegno quotato



## Caratteristiche dei montanti e capacità residue

| Full Visibility Duplex (FVD)                                |    | FVD 33 | FVD 37 | FVD 40 |
|-------------------------------------------------------------|----|--------|--------|--------|
| Mast/fork carriage tilt, forward                            | °  | 6      | 6      | 6      |
| Mast/fork carriage tilt, backward                           | °  | 12     | 12     | 12     |
| h1 - Mast lowered height                                    | mm | 2200   | 2450   | 2650   |
| h2 - Mast free lift                                         | mm | 145    | 145    | 145    |
| h3 - Mast lifting height                                    | mm | 3300   | 3700   | 4000   |
| h4 - Mast extended height                                   | mm | 4035   | 4435   | 4735   |
| Residual capacity at max height                             | kg | 3300   | 3000   | 3000   |
| Residual capacity with integrated side shift at max heighth | kg | 3300   | 3000   | 3000   |
| Height at max capacity                                      | mm | 3300   | 3700   | 4000   |
| Height at max capacity with integrated sideshift            | mm | 3300   | 3700   | 4000   |

| Free Lift Duplex (FLD)                                      |    | FLD 33 | FLD 37 | FLD 40 |
|-------------------------------------------------------------|----|--------|--------|--------|
| Mast/fork carriage tilt, forward                            | °  | 6      | 6      | 6      |
| Mast/fork carriage tilt, backward                           | °  | 12     | 12     | 12     |
| h1 - Mast lowered height                                    | mm | 2230   | 2430   | 2580   |
| h2 - Mast free lift                                         | mm | 1475   | 1675   | 1825   |
| h3 - Mast lifting height                                    | mm | 3300   | 3700   | 4000   |
| h4 - Mast extended height                                   | mm | 4055   | 4455   | 4755   |
| Residual capacity at max height                             | kg | 3000   | 3000   | 3000   |
| Residual capacity with integrated side shift at max heighth | kg | 3000   | 3000   | 3000   |
| Height at max capacity                                      | mm | 3300   | 3700   | 4000   |
| Height at max capacity with integrated sideshift            | mm | 3300   | 3700   | 4000   |

| Free Lift Triplex (FLT)                                     |    | FLT 43 | FLT 45 | FLT 47 | FLT 48 | FLT 50 | FLT 55 | FLT 60 | FLT 65 |
|-------------------------------------------------------------|----|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward                            | °  | 6      | 6      | 6      | 6      | 6      | 3      | 3      | 3      |
| Mast/fork carriage tilt, backward                           | °  | 6      | 6      | 6      | 6      | 6      | 6      | 6      | 6      |
| h1 - Mast lowered height                                    | mm | 2115   | 2165   | 2215   | 2265   | 2315   | 2515   | 2765   | 2915   |
| h2 - Mast free lift                                         | mm | 1360   | 1410   | 1460   | 1510   | 1560   | 1760   | 2010   | 2160   |
| h3 - Mast lifting height                                    | mm | 4300   | 4500   | 4700   | 4800   | 5000   | 5500   | 6000   | 6500   |
| h4 - Mast extended height                                   | mm | 5055   | 5305   | 5455   | 5555   | 5755   | 6255   | 6805   | 7255   |
| Residual capacity at max height                             | kg | 2950   | 2900   | 2800   | 2800   | 2500   | 1850   | 1400   | 1300   |
| Residual capacity with integrated side shift at max heighth | kg | 2850   | 2800   | 2700   | 2700   | 2400   | 1750   | 1300   | 1250   |
| Height at max capacity                                      | mm | 4000   | 4000   | 4000   | 4000   | 4000   | 4000   | 4000   | 2500   |
| Height at max capacity with integrated sideshift            | mm | 4000   | 4000   | 4000   | 4000   |        |        |        |        |



**Sede centrale**

MANITOU ITALIA Srl

Via Cristoforo Colombo 2, Loc. Cavazzona - 41013 CASTELFRANCO EMILIA (MO)

Tel: 059.95.98.11 - Fax 059.95.98.65

[www.manitou.com](http://www.manitou.com)



Questa pubblicazione presenta la descrizione delle versioni e delle possibilità di configurazione dei prodotti Manitou, che possono differire per attrezzature. Gli allestimenti presentati nel presente opuscolo possono essere di serie, optional o non disponibili, a seconda delle versioni. Manitou si riserva il diritto di modificare, in qualsiasi momento e senza alcun preavviso, le specifiche tecniche descritte e rappresentate. Le specifiche indicate non rappresentano alcun obbligo per il costruttore. Per maggiori dettagli, rivolgersi al proprio concessionario Manitou. Documento non contrattuale. Elenco delle specifiche non esaustivo. I loghi nonché l'identità visiva dell'azienda sono di proprietà di Manitou e non possono essere utilizzati senza autorizzazione. Tutti i diritti riservati. Le immagini e gli schemi contenuti nel presente opuscolo sono forniti esclusivamente a fini di consultazione e a titolo indicativo.

Manitou BF SA - Società anonima con consiglio di amministrazione. Capitale sociale: 39,668,399 euro - 857 802 508 RCS Nantes