

Technical sheet :


MLA 2-25 H



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Metric |
|--|-----|---------------------------------|
| Static tipping load with bucket (straight) | | 1015 kg |
| Static tipping load with bucket (full turn) | | 865 kg |
| Static tipping load with forks (straight) | | 740 kg |
| Static tipping load with forks (full turn) | | 630 kg |
| Max. height of bucket pivot point | h35 | 2736 mm |
| Weight and dimensions | | |
| Unladen weight (with forks) with 4-post canopy | | 1740 kg |
| Wheelbase | y | 1419 mm |
| Overall cab width | b4 | 991 mm |
| Overall height with 4 posts canopy | h38 | 2140 mm |
| Dump reach - Full height | r6 | 475 mm |
| Hood Height | h40 | 1254 mm |
| Overall Operating Height - Fully Raised | h27 | 3535 mm |
| Articulation angle | a19 | 45 ° |
| Maximum oscillation angle | | 11 ° |
| Overall length with bucket | l16 | 3627 mm |
| Overall width less bucket | b1 | 1040 mm |
| Overall length - Less Bucket | l2 | 2928 mm |
| Rear overhang | c6 | 801 mm |
| Dump angle - Fully raised | a5 | 41 ° |
| Dump Height - Fully Raised | h29 | 2008 mm |
| Maximum Rollback Angle - Fully Raised | a4 | 45 ° |
| Digging Position | h32 | -45 mm |
| Ground clearance | m4 | 153 mm |
| Clearance Radius - Front with Bucket | b18 | 2681 mm |
| Clearance Radius - Less bucket | b14 | 2251 mm |
| Ground Plane to Bucket Edge Height | h42 | 2515 mm |
| Tread width (wheel center) | b29 | 848 mm |
| Attachment Pivot Clearance | | 192 mm |
| Height from ground to axle center | m8 | 144 mm |
| Bucket Width | e1 | 1100 mm |
| Front Wheel Center to Pivot Pin | m3 | 563 mm |
| Height to Hinge Pin - Fully Raised | h28 | 2736 mm |
| Engine | | |
| Engine brand | | Perkins |
| Engine model | | 403J-11 |
| Engine nom | | Stage V |
| Number of cylinders | | 3 |
| I.C. Engine power rating / Power | | 24.70 Hp / 18.40 kW |
| Max. torque / Engine rotation | | 66.80 Nm / 2100 rpm |
| Engine cooling system | | Water |
| Transmission | | |
| Transmission type | | Hydrostatic with 4 wheel motors |
| Number of gears (forward / reverse) | | 1 / 1 |
| Max. travel speed (may vary according to applicable regulations) | | 12 km/h |
| Service brake | | Inching Brake |
| Hydraulics | | |
| Hydraulic pump type | | Gear pump |
| Hydraulic flow - Pressure | | 30 l/min / 207 bar |
| High-Flow Option (l/min) | | 30 l/min |
| Tank capacities | | |
| Hydraulic oil | | 24 l |
| Fuel tank | | 30 l |

MLA 2-25 H - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes