Technical sheet:


MLA 5-50 H






| | MLA 5-50 H | Created on May 3, 2025 at 12:19 PM UT |
|--|------------|---|
| Capacities | | Metric |
| Static tipping load with bucket (straight) | | 1880 kg |
| Static tipping load with bucket (full turn) | | 1650 kg |
| Static tipping load with forks (straight) | | 1470 kg |
| Static tipping load with forks (full turn) | | 1295 kg |
| Max. height of bucket pivot point | h35 | 3070 mm |
| Weight and dimensions | | |
| Unladen weight (with forks) with 4-post canopy | | 2678 kg |
| Wheelbase | у | 1770 mm |
| Overall cab width | b4 | 991 mm |
| Overall height with 4 posts canopy | h38 | 2290 mm |
| Dump reach - Full height | r6 | 458 mm |
| Hood Height | h40 | 1469 mm |
| Overall Operating Height - Fully Raised | h27 | 3870 mm |
| Articulation angle | a19 | 40 ° |
| Maximum oscillation angle | | 11 ° |
| Overall length with bucket | 116 | 4490 mm |
| Overall width less bucket | b1 | 1330 mm |
| Overall length - Less Bucket | 12 | 3792 mm |
| Rear overhang | c6 | 1146 mm |
| Dump angle - Fully raised | a5 | 47 ° |
| Dump Height - Fully Raised | h29 | 2301 mm |
| Maximum Rollback Angle - Fully Raised | a4 | 46 ° |
| Digging Position | h32 | -72 mm |
| Ground clearance | m4 | 356 mm |
| Clearance Radius - Front with Bucket | b18 | 3361 mm |
| Clearance Radius - Less bucket | b14 | 2888 mm |
| Ground Plane to Bucket Edge Height | h42 | 2837 mm |
| Tread width (wheel center) | b29 | 946 mm |
| Attachment Pivot Clearance | , | 168 mm |
| Height from ground to axle center | m8 | 230 mm |
| Bucket Width | e1 | 1520 mm |
| Front Wheel Center to Pivot Pin | m3 | 733 mm |
| Height to Hinge Pin - Fully Raised | h28 | 3070 mm |
| Engine | | |
| Engine brand | | Perkins |
| Engine model | | 403J-E17T |
| Engine norm | | Stage V |
| Number of cylinders | | 3 |
| I.C. Engine power rating / Power | | 48 Hp / 36 kW |
| Max. torque / Engine rotation | | 166 Nm / 1600 rpm |
| Engine cooling system | | Water |
| Transmission | | |
| Transmission type | | Hydrostatic |
| Number of gears (forward / reverse) | | 2 / 2 |
| Max. travel speed (may vary according to applicable regulations) | | 20 km/h |
| Max. travel speed (in option) (may vary according to applicable regulations) | | 30 km/h |
| | | Hydraulic drum brake on front axle, acting on all 4 |
| Service brake | | wheels |
| Hydraulics | | |
| Hydraulic pump type | | Gear pump |
| Hydraulic flow - Pressure | | 60 I/min / 207 bar |
| High-Flow Option (I/min) | | 60 l/min |
| Tank capacities | | |
| Hydraulic oil | | 50 I |
| Fuel tank | | 65 I |

MLA 5-50 H - Dimensional drawing









Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes