

Technical sheet :

MSI-X 30



 **MANITOU**
HANDLING YOUR WORLD

Technical drawings of a forklift showing top and side views with dimension labels.

Top View:

- $b1$: Overall width of the forklift.
- $b3$: Width of the mast.
- $b10$: Width of the fork.
- e : Distance from the center of the fork to the center of the mast.
- $b11$: Width of the rear section.
- Wa : Angle of the mast.
- 100 : Distance from the front of the forklift to the center of the mast.
- Ast : Overall length of the forklift.

Side View:

- $h4$: Height of the mast.
- $h3$: Height of the mast at the fork.
- $h1$: Height of the mast at the fork.
- c : Distance from the center of the fork to the center of the mast.
- $h2$: Height of the fork.
- $h6$: Overall height of the forklift.
- $h10$: Height of the rear section.
- l : Distance from the front of the forklift to the center of the mast.
- $m1$: Distance from the center of the mast to the center of the rear wheel.
- x : Distance from the center of the rear wheel to the center of the front wheel.
- $m2$: Distance from the center of the front wheel to the center of the rear wheel.
- y : Distance from the center of the rear wheel to the center of the front wheel.
- $l2$: Overall length of the forklift.

Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 37	FVD 40	FVD 45
α - Mast/fork camiage tilt, forward	°	10	10	10	10	10
β - Mast/fork camiage tilt, backward	°	12	12	12	12	12
h1 - Mast lowered height	mm	2136	2286	2546	2736	2986
h2 - Mast free lift	mm	90	90	90	90	90
h3 - Mast lifting height	mm	3000	3300	3700	4000	4500
h4 - Mast extended height	mm	3738	4038	4438	4738	5238
Residual capacity at max height	kg	3000	3000			
Height at max capacity	mm	3000	3300	2500	2500	2500

Free Lift Triplex (FLT)		FLT 34	FLT 37	FLT 40	FLT 43	FLT 47	FLT 55	FLT 60
α - Mast/fork camiage tilt, forward	°	10	10	10	10	10	6	6
β - Mast/fork camiage tilt, backward	°	12	12	12	12	12	6	6
h1 - Mast lowered height	mm	1936	2036	2136	2286	2386	2736	2986
h2 - Mast free lift	mm	1208	1308	1408	1558	1658	2008	2258
h3 - Mast lifting height	mm	3400	3700	4000	4300	4700	5500	6000
h4 - Mast extended height	mm	4184	4484	4784	5084	5484	6284	6784
Residual capacity at max height	kg	3000						
Height at max capacity	mm	3400	2500	2500	2500	2500	2500	2500

Full Visibility Triplex (FVT)		FVT 33
h1 - Mast lowered height	mm	1826
h2 - Mast free lift	mm	77
h3 - Mast lifting height	mm	3300
h4 - Mast extended height	mm	4027
Height at max capacity	mm	2500



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes