Technical sheet:

# MT 1840 HA







	<b>мт 1840 на</b> Created on November 8, 2025 at 10:13 РМ U
Capacities	Metric
Max. capacity	4000 kg
Max. lifting height	17.55 m
Maximum outreach	13.08 m
Breakout force with bucket	8390 daN
Weight and dimensions	3000 dair
Overall length to carriage	l11 6.15 m
Length to face of forks	
Overall width	b1 2.36 m
Overall height	h17 2.45 m
Wheelbase	y 3.07 m
Ground clearance	m4 0.37 m
Overall cab width	b4 0.89 m
Tilt-up angle	a4 12 °
Tilt-down angle	a5 114°
External turning radius (over tyres)	Wa1 3.94 m
Unladen weight (with forks)	12680 kg
Overall weight	12680 kg
Tires type	Inflatable
Standard tires	Alliance 400/80 - 24 - 162A8
Forks length / width / section	I / e / s 1200 mm x 125 mm x 50 mm
Performances	
Lifting	14 s
Lowering	14 s
Extension	19 s
Retraction	15 s
Scoop	5 s
Dump	5 s
Engine	
	Deutz
Engine brand	
Engine norm	Stage V
Engine model	TCD 3.6
Number of cylinders / Capacity of cylinders	4 - 3621 cm³
Engine power (Hp/kW)	100 Hp / 75 kW
Max. torque / Engine rotation	410 Nm @ 1600 rpm
Drawbar pull (Laden)	7350 daN
Transmission	
Transmission type	Hydrostatic
Number of gears (forward / reverse)	3/3
Max. travel speed	24.90 km/h
Max. travel speed (may vary according to applicable regulations)	24.90 km/h
Parking brake	Automatic negative parking brake
Service brake	Oil-immersed multi-discs on front & rear axles
Hydraulics	
Hydraulic pump type	Gear pump
Hydraulic flow / Pressure	167 l/min-250 bar
Tank capacities	
Engine oil	101
Hydraulic oil	1351
Diesel Exhaust fluid (AdBlue® type)	22.60
Fuel	140
Noise and vibration	140 1
	79 dB
Noise at driving position (LpA)	
Noise to environment (LwA)	106 dB
Vibration on hands/arms	< 2.50 m/s²
Miscellaneous	
Steering wheels (front / rear)	2/2
Drive wheels (front / rear)	2/2
Cab certification	Cabin ROPS - FOPS level 2
Controls	JSM
Additional information	Data indicated with basket basket, except max.
. Identification	capacity, lifting height and offset.

Data indicated with basket basket, except max. capacity, lifting height and offset.

# MT 1840 HA - Dimensional drawing








### MT 1840 HA - Load chart


Machine on tires with forks - with levelling device Metric

### 14 40° 13 12 11 10 30° 9 8 7 20° 6 4 10° 3 2 0° 0 10° 3 2 0° 0 10° 3 2 0° 0 10° 3 2 0° 0 10° 3 2 0° 0 10° 3 2 10° 0

### Machine on lowered stabilisers with forks Metric



# Machine on stabilisers with Man basket Metric







### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes