Technical sheet:

MLA-T 516-75 H





	MLA-1 316-73 H U	reated on October 19, 2025 at 12:27 PM U	
Capacities		Metric	
Static tipping load with bucket (straight)		3535 kg	
Static tipping load with forks (straight)		2732 kg	
Static tipping load with forks (full turn)		2000 kg	
Max. payload with forks as per EN 474-3 (80%)		1600 kg	
Max. height of bucket pivot point	h35	5.03 m	
Max. lifting height (below forks)	h3	4.84 m	
Maximum outreach		3.30 m	
Weight and dimensions			
Unladen weight (with forks) with 4-post canopy		5543 kg	
Overall width of 4 posts canopy	b22	1.28 m	
Overall cab width	b4	1.28 m	
Overall height with 4 posts canopy	h38	2.48 m	
Articulation angle	a19	44 °	
Overall width less bucket	b1	1.74 m	
Overall length - Less Bucket	12	4.95 m	
Ground clearance	m4	0.31 m	
Engine		0.51 111	
Engine brand		Deutz	
Engine model		TD 3.6 L4	
Engine nom			
Number of cylinders / Capacity of cylinders		Stage V, Tier 4	
Engine power (Hp / kW)		4 - 3600 cm ³	
- , , , ,		74.30 Hp / 55.40 kW	
Max. torque / Engine rotation		330 Nm / 1600 rpm	
Engine cooling system Transmission		2 radiators water + hydraulic oil	
		Understatio	
Transmission type		Hydrostatic 2 / 2	
Number of gears (forward / reverse)			
Max. travel speed (may vary according to applicable regulations)		30 km/h	
Travel speed (laden)		20 km/h	
Differential lock		Front and rear locking of the machine	
Parking brake		Manual	
Service brake		Hydraulic drum brake on front axle, acting on all wheels	
Hydraulics			
Hydraulic pump type		Gear pump	
Hydraulic flow - Pressure		70 l/min / 200 bar	
High-Flow Option (I/min)		110 l/min	
Drive hydraulic system pressure		380 bar	
Tank capacities		300 Bui	
Hydraulic oil		74	
Fuel tank		102 l	
Noise and vibration		1021	
Vibration on hands/arms		< 2.50 m/s²	
		< 2.50 III/8°	
Miscellaneous Cab certification		ROPS - FOPS cab (level 1)	


Options / Finishing

S: Standard / O: Optional / -: Not available

	Essential	Classic	Premium
Lifting function			
Attachment hydraulic line	S	S	S
Boom suspension	0	0	S
Easy Connect System (ECS)	S	•	-
Hydraulic attachment locking	S	S	S
Operator station			
Adjustable and telescopic steering column	S	S	S
Air conditioning with manual adjustment	-		S
Air prefilter	S	•	-
Air suspension seat	-	0	S
Canopy	S	•	-
Closed cab with heating	-	•	S
Floor mat	S	S	S
Manual air conditioning	-	0	-
Suspension Seat - Mechanical	S	-	-
Tuner car radio - 50W	-	S	S
Motorization/Power			
Continuous flow hydraulics	S	S	S
Hand throttle	S	S	S
Self cleaning air prefilter	-	S	S
Simultaneous movements flow sharing distributor	S	S	S
Speed control	0	0	S
Third speed	0	0	S
Lighting			
Complete road lighting	0	•	S
Front and rear LED work lights on cab (x4 : 2 front + 2 rear)	0	0	S
Front and rear work lights on cab (x4)	\$/0**	S	-


MLA-T 516-75 H - Load chart


Machine on tires with forks - Load chart compliant with EN 474-3 (80%) Metric



MLA-T 516-75 H - Dimensional drawing











Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes