

Technical sheet :

# 1050R

---



 **MANITOU**  
HANDLING YOUR WORLD

| Capacities   |     | Imperial                |
|--|-----|-------------------------|
| Rated Operating Capacity                             |     | 1049 lb                 |
| Rated Operating Capacity with Optional Counterweight |     | 1175 lb                 |
| Unladen weight                                       |     | 4200 lb                 |
| Weight and dimensions                                |     |                         |
| Wheelbase  | y   | 34 in                   |
| Overall Operating Height - Fully Raised              | h27 | 140 in                  |
| Height to Hinge Pin - Fully Raised                   | h28 | 108 in                  |
| Overall Height to top of ROPS                        | h17 | 70 in                   |
| Dump angle at full height                            | a5  | 42 °                    |
| Dump height  | h29 | 84 in                   |
| Overall length with bucket                           | l16 | 114 in                  |
| Dump reach - Full height                             | r6  | 23 in                   |
| Rollback at ground                                   | a13 | 29 °                    |
| Seat to ground height                                | h30 | 33 in                   |
| Overall width less bucket                            | b1  | 48 in                   |
| Bucket Width   | e1  | 55 in                   |
| Ground clearance                                     | m4  | 6 in                    |
| Overall length - Less Bucket                         | l2  | 89 in                   |
| Departure angle                                      | a2  | 26 °                    |
| Clearance Radius - Front with Bucket                 | b18 | 69 in                   |
| Performances   |     |                         |
| Travel speed (unladen)                               |     | 6 mph                   |
| Wheels   |     |                         |
| Standard tires                                       |     | 27 x 8.5 x 15 HD        |
| Engine   |     |                         |
| Engine brand   |     | Yanmar                  |
| Engine model   |     | 3TNV88C-KMSV            |
| Engine norm  |     | Stage V, Tier 4         |
| Gross Power  |     | 25.50 kW                |
| Net Power  |     | 24.70 kW                |
| Max. torque / Engine rotation                        |     | 80 ft/lbs / 2800 rpm    |
| Power source   |     | Diesel                  |
| I.C. Engine power rating                             |     | 34.20 Hp                |
| Battery voltage                                      |     | 12 V                    |
| Alternator   |     | 40 kW                   |
| Starter  |     | 2.30 kW                 |
| Hydraulics   |     |                         |
| Standard flow - Auxiliary hydraulics                 |     | 15 US gpm               |
| Auxiliary Hydraulic Pressure                         |     | 2750 PSI                |
| Tank capacities                                      |     |                         |
| Fuel tank  |     | 10 US gal               |
| Hydraulic tank capacity                              |     | 8 US gal                |
| Displacement   |     | 0.42 US gal             |
| Noise and vibration                                  |     |                         |
| Noise to environment (LWA)                           |     | 101 dB                  |
| Noise at driving position (LpA)                      |     | 80 dB                   |
| Whole-Body Vibration (ISO 2631-1)                    |     | 0.81 m/s <sup>2</sup>   |
| Vibration on hands/arms                              |     | < 0.93 m/s <sup>2</sup> |

### 1050R - Dimensional drawing



# Equipment

|  |          |
|--|----------|
| —  |          |
| Integral Access Plate (removable)                | Standard |
| <b>Lifting function</b>                          |          |
| All-Tach® Attachment Mounting System             | Standard |
| Auxiliary Hydraulics                             | Standard |
| <b>Lighting</b>                                  |          |
| Work Lights - Front and Rear                     | Standard |
| <b>Motorization/Power</b>                        |          |
| Engine Block Heater                              | Standard |
| <b>Operator station</b>                          |          |
| Cab Enclosure                                    | Optional |
| Foot and Hand Throttles 2                        | Standard |
| Gehl T-Bar Controls                              | Standard |
| Hand/Foot Controls                               | Standard |
| Heating  | Optional |
| High-Back Adjustable Seat                        | Standard |
| Horn   | Optional |
| ROPS/FOPS Level II Overhead Guard                | Standard |
| Sound Reduction Material                         | Standard |
| Suspension Seat - Mechanical                     | Optional |
| <b>Other options</b>                             |          |
| Hydrostatic Drive - Servo                        | Standard |
| Selectable Self-Leveling Hydraulic Lift Action 4 | Optional |
| <b>Secondary functions</b>                       |          |
| Counterweight                                    | Optional |
| Full Instrumentation                             | Standard |
| <b>Security</b>                                  |          |
| Anti-Vandalism Protection                        | Standard |
| Back-Up Alarm                                    | Optional |
| Brake Control (Auto / Manual)                    | Standard |
| Hydraloc™ Safety System                          | Standard |
| Lift Arm Support Device                          | Standard |
| Operator Restraint Bar                           | Standard |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes