

Technical sheet :


MTA 10044 SERIES IV



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric	
Max. capacity		4535.93 kg	
Max. lifting height		13.42 m	
Maximum outreach		9.30 m	
Weight and dimensions			
Overall length to carriage	l11	6.10 m	
Overall width	b1	2.53 m	
Overall height	h17	2.41 m	
Wheelbase	y	3.15 m	
Ground clearance	m4	457 mm	
Overall cab width	b4	838 mm	
Tilt-up angle	a4	12 °	
Tilt-down angle	a5	112 °	
External turning radius	Wa3	4.24 m	
Unladen weight (with forks)		11476 kg	
Standard tires		14 x 24	
Frame leveling longitudinal +/-		10 °	
Frame leveling corrector	a9	10 °	
Performances			
Lifting		15 s	
Lowering		10 s	
Extension		15 s	
Retraction		12 s	
Crown		6 s	
Dump		3 s	
Engine			
Engine brand		Deutz	
Engine norm		Tier 4 final	
Engine model		TCD 3.6 L4	
Number of cylinders / Capacity of cylinders		4 - 3.80 cm³	
Engine power (Hp/kW)		119.35 Hp / 89 kW	
Max. torque		480 Nm	
Transmission			
Transmission type		Torque converter with powershift gearbox	
Number of gears (forward / reverse)		4 / 3	
Max. travel speed		32.30 km/h	
Parking brake		Hydraulic spring release SAHR	
Service brake		Wet disc brakes	
Axle Manufacturer		Dana	
Hydraulics			
Hydraulic pump type		Gear pump	
Hydraulic flow / Pressure		157 l/min-207 bar	
Tank capacities			
Engine oil		14.70 l	
Hydraulic oil		170 l	
Diesel Exhaust fluid (AdBlue® type)		19 l	
Fuel		178 l	
Miscellaneous			
Steering wheels (front / rear)		2 / 2	
Drive wheels (front / rear)		2 / 2	
Cab certification		ROPS/FOPS	
Controls		Single Joystick FNR	

MTA 10044 Series IV - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes