Technical sheet:


## MTA 10044 SERIES IV





Capacities		Metric
Max. capacity		4535.93 kg
Max. lifting height		13.42 m
Max. outreach		9.30 m
Weight and dimensions		
Overall length to carriage	l11	6.10 m
Overall width	b1	2.53 m
Overall height	h17	2.41 m
Wheelbase	у	3.15 m
Ground clearance	m4	457 mm
Overall cab width	b4	838 mm
Filt-up angle	a4	12 °
	a5	112 °
Tilt-down angle		
External tuming radius	Wa3	4.24 m
Jnladen weight (with forks)		11476 kg
Standard tires		14 x 24
Frame leveling longitudinal +/-		10 °
Frame leveling corrector	a9	10 °
Performances		
Lifting		15 s
_owering		10 s
Extension		15 s
Retraction		12 s
Crowd		6 s
Dump		3 s
Engine		
Engine brand		Deutz
Engine norm		Tier 4 final
Engine model		TCD 3.6 L4
Number of cylinders / Capacity of cylinders		4 - 3.80 cm <sup>3</sup>
I.C. Engine power rating - Power		119.35 Hp / 89 kW
Max. torque		480 Nm
Transmission		
Transmission type		Torque converter with powershift gearbox
Number of gears (forward / reverse)		4/3
Max. travel speed		32.30 km/h
Parking brake		SAHR
Service brake		Wet disc brakes
Axle Manufacturer		Dana
Hydraulics		Dalla
Hydraulic pump type		Gear pump
Hydraulic pump type Hydraulic flow / Pressure		157 l/min-207 bar
•		137 I/IIIII1-207 Ddi
Tank capacities		14.70 [
Engine oil		14.70
Hydraulic oil		170
Fuel tank		178 l
DEF tank capacity		19 l
Miscellaneous		
Steering wheels (front / rear)		2/2
Drive wheels (front / rear)		2 / 2
		ROPS/FOPS

## MTA 10044 Series IV - Dimensional drawing







## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes