Technical sheet:


MTA 10055 E74






	MTA 10055 E74	Created on October 30, 2025 at 8:25 AM UTC
Capacities		Imperial
Max. capacity		10000 lb
Max. lifting height		55 ft 1 in
Maximum outreach		41 ft 2 in
Weight and dimensions		
Overall length to carriage	l11	21 ft
Overall width	b1	8 ft 4 in
Overall height	h17	8 ft 6 in
Wheelbase	у	10 ft 4 in
Ground clearance	m4	18 in
Overall cab width	b4	33 in
Tilt-up angle	a4	12 °
Tilt-down angle	a5	112 °
External turning radius	Wa3	13 ft 11 in
Unladen weight (with forks)		27800 lb
Overall weight		27800 lb
Standard tires		14 x 24
Frame leveling longitudinal +/-		10 °
Frame leveling corrector	a9	10 °
Performances	47	10
Lifting		15 s
Lowering		10 s
Extension		15 s
Retraction		12 s 10 s
Crowd		
Dump		5 s
Engine		
Engine brand		Deutz
Engine norm		Stage IV, Tier 4 final
Engine model		TCD 3.6 L4
Engine power (Hp/kW)		73.75 Hp / 55 kW
Max. torque / Engine rotation		288 ft/lbs @ 1300 rpm
Transmission		
Transmission type		Powershift
Number of gears (forward / reverse)		4/3
Max. travel speed		15 mph
Parking brake		Hydraulic spring release SAHR
Service brake		Wet disc brakes
Axle Manufacturer		Dana
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow / Pressure		41 US gpm-3002 PSI
Tank capacities		
Engine oil		4 US gal
Hydraulic oil		45 US gal
Fuel tank		47 US gal
Miscellaneous		
Steering wheels (front / rear)		2 / 2
Drive wheels (front / rear)		2 / 2
Cab certification		ROPS/FOPS
Controls		Single Joystick FNR

MTA 10055 E74 - Dimensional drawing



MTA 10055 E74 - Load chart

Machine on lowered stabilisers with forks Imperial







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes