Technical sheet:

MTA 1055







	MTA 1055	Created on October 22, 2025 at 3:48 PM UTC
Capacities		Imperial
Max. capacity		10000 lb
Max. lifting height		55 ft 7 in
Maximum outreach		42 ft 3 in
Weight and dimensions		
Length to face of forks	12	21 ft
Overall length (with forks)	I1	25 ft
Overall width	b1	8 ft 4 in
Overall height	h17	8 ft 6 in
Wheelbase	у	11 ft 6 in
Ground clearance	, m4	1 ft 7 in
Overall cab width	b4	3 ft 1 in
Tilt-up angle	a4	34 °
Tilt-down angle	a5	96 °
External turning radius	Wa3	12 ft 10 in
Overall weight	Was	30300 lb
Tires type		Pneumatic
	1/e/s	48 in x 5 in x 2 in
Forks length / width / section		46 III X 5 III X 2 III
Frame leveling corrector	a9	10
Performances		17 :
Lifting		16 s
Lowering		11 s
Extension		18 s
Retraction		16 s
Crowd		4 s
Dump		6 s
Engine		
Engine brand		Deutz
Engine norm		Tier 4 final
Engine model		TCD 3.6 L4
Number of cylinders / Capacity of cylinders		4 - 220 in³
Engine power (Hp/kW)		127 Hp / 95 kW
Max. torque / Engine rotation		369 ft/lbs @ 2300 rpm
Drawbar pull		12519 daN
Transmission		
Transmission type		Powershift
Number of gears (forward / reverse)		5 / 3
Max. travel speed		20 mph
Parking brake		Hydraulic spring release SAHR
Service brake		Wet disc brakes
Hydraulics		
Hydraulic pump type		Axial piston
Hydraulic flow / Pressure		40 US gpm-4000 PSI
Tank capacities		
Engine oil		2 US gal
Hydraulic oil		42 US gal
Diesel Exhaust fluid (AdBlue® type)		4 US gal
Fuel tank		38 US gal
Noise and vibration		
Noise at driving position (LpA)		80 dB
Miscellaneous		
Steering wheels (front / rear)		2/2
Drive wheels (front / rear)		2/2
Controls		Joystick
		30,000.

MTA 1055 - Dimensional drawing








MTA 1055 - Load chart

Machine on tires with forks Imperial

40°, 30° 20°_25 3000 lb 4000 lb 6000 lb 8000 lb 2000 lb 0 ft

Machine on lowered stabilisers with forks Imperial







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes