

Technical sheet :




MTA 842 E74



 **MANITOU**
HANDLING YOUR WORLD


Capacities		Metric	
Max. capacity		3628.70 kg	
Max. lifting height		12.96 m	
Maximum outreach		8.69 m	
Weight and dimensions			
Overall length to carriage		I11	6.30 m
Length to face of forks		I2	6.29 m
Overall length (with forks)		I1	7.51 m
Overall width		b1	2.48 m
Overall height		h17	2.44 m
Wheelbase		y	3.50 m
Ground clearance		m4	0.46 m
Overall cab width		b4	0.95 m
Tilt-up angle		a4	34 °
Tilt-down angle		a5	96 °
External turning radius		Wa3	4 m
Unladen weight			10864 kg
Tires type			Pneumatic
Forks length / width / section		I / e / s	1219 mm x 101 mm x 50.80 mm
Frame leveling corrector		a9	
Performances		10 °	
Lifting			11 s
Lowering			6 s
Extension			17 s
Retraction			11 s
Crown			4 s
Dump			6 s
Engine			
Engine brand			Deutz
Engine norm			Tier 4 final
Engine model			TCD 3.6 L4
Number of cylinders / Capacity of cylinders			4 - 3600 cm³
Engine power (Hp/kW)			74 Hp / 55 kW
Max. torque / Engine rotation			390 Nm @ 2300 rpm
Drawbar pull			10614 kgF
Transmission			
Transmission type			Powershift
Number of gears (forward / reverse)			5 / 3
Max. travel speed			32 km/h
Parking brake			Hydraulic spring release SAHR
Service brake			Wet disc brakes
Hydraulics			
Hydraulic pump type			Axial piston
Hydraulic flow / Pressure			151 l/min-275.80 bar
Tank capacities			
Engine oil			8.51 l
Hydraulic oil			136.30 l
Fuel			144 l
Noise and vibration			
Noise at driving position (LpA)			80 dB
Miscellaneous			
Steering wheels (front / rear)			2 / 2
Drive wheels (front / rear)			2 / 2

MTA 842 E74 - Dimensional drawing



MTA 842 E74 - Load chart

Machine on tires with forks Metric





MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes