

# V210

## COMPACT LOADERS

**GEHL**®



### KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

### KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2032 mm (80")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 249 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3061 mm (120.5") height to hinge pin
- ✓ 1623 mm (63.9") machine width - less bucket
- ✓ 3393 kg (7,480 lbs.) operating weight

		METRIC
CAPACITIES	Operating Capacity At 50% Tipping Load	952.54 kg
	Operating Weight	3393 kg
	Unladen weight	3055 kg
	Tipping capacity	1905 kg
WEIGHT AND DIMENSIONS	Wheelbase	1092 mm
	Overall Operating Height - Fully Raised	4059 mm
	Height to Hinge Pin - Fully Raised	3061 mm
	Overall Height to top of ROPS	2032 mm
	Dump angle at full height	42 °
	Dump height	2286 mm
	Overall length with bucket	3543 mm
	Dump reach - Full height	851 mm
	Rollback Angle at Full Height	92 °
	Seat to ground height	952.50 mm
	Overall width less bucket	1623 mm
	Ground clearance	178 mm
	Overall length - Less Bucket	2743 mm
	Clearance Radius - Front with Bucket	2146 mm
	Rear departure angle	25 °
PERFORMANCES	Travel speed (unladen)	12.10 km/h
	Travel Speed with Two-Speed Option - Maximum	18.70 km/h
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98C-NGL
	Engine nom	Stage V
	Max. torque / Engine rotation	241 Nm / 1625 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine power (Hp / kW)	72 Hp / 51.70 kW
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
TANK CAPACITIES	Fuel	106 l
	Hydraulic tank capacity	22.70 l
	Displacement	3.30 l

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



## STANDARD FEATURES

- Battery Disconnect
- Back-Up Alarm
- Hand throttle
- Horn
- Auxiliary Hydraulics
- Engine Block Heater
- 4 point lift
- Rear Lights
- Sound reduction Package
- Lift Arm Support Device
- Integral Access Plate (removable)
- Operator Restraint Bar
- Anti-Vandalism Protection
- Single Flange Front/Dual Flange Rear Idlers
- IdealTrax® automatic track tensioning system
- 12Volt Power Port
- High-Back Adjustable Seat
- Brake Control (Auto / Manual)
- LED Work Lights
- All-Tach® Attachment Mounting System

## OPTIONAL FEATURES

- High-Flow Auxiliary Hydraulics
- Cab Enclosure
- Power-A-Tach® Attachment Mounting System
- Inner rear view mirror
- Sliding Side Windows
- Air Conditioning
- Swing-out Cab Door
- ROPS/FOPS Level II Overhead Guard
- Bluetooth car radio
- Selectable Self-Leveling Hydraulic Lift Action



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT