SKID LOADERS



GEHL®

	V210 - NEW ETSLEILL	v210 - NEW Erstellt am 5. Mai 2024 um 19:30:18 UTC	
Capacities		Metrisch	
Operating Capacity At 50% Tipping Load		952.54 kg	
Operating Weight		3393 kg	
Unladen weight		3045 kg	
Tipping capacity		1905 kg	
Weight and dimensions			
Operating Weight - Approximate		3393 kg	
Overall Operating Height - Fully Raised	h27	4013 mm	
Height to Hinge Pin – Fully Raised	h28	3061 mm	
Overall Height to top of ROPS	h17	2032 mm	
Dump angle at full height	a5	42 °	
Dump height	h29	2286 mm	
Overall length with bucket	l16	3543 mm	
Dump reach - Full height	r6	851 mm	
Rollback Angle at Full Height	a4	92 °	
Seat to ground height	h30	952.50 mm	
Overall width less bucket	b1	1623 mm	
Ground clearance	m4	178 mm	
Overall length - Less Bucket	l2	2743 mm	
Clearance Radius - Front with Bucket	b18	2146 mm	
Clearance Circle - Rear	wa1	1664 mm	
Performances			
Travel Speed with Two-Speed Option - Maximum		18.70 km/h	
Travel speed (unladen)		12.10 km/h	
Engine			
Engine brand		Yanmar	
Engine model		4TNV98C-NGL	
Engine norm		Stage V, Tier 4	
Gross Power		52.70 kW	
Net Power		51.70 kW	
Max. torque / Engine rotation		241 Nm / 1625 rpm	
Power source		Diesel	
Number of cylinders		4	
Engine cooling system		Water	
Battery voltage		12 V	
Alternator - Ampere		100 A	
Starter		3 kW	
Hydraulics		5	
Standard flow - Auxiliary hydraulics		86.50 l/min	
Auxiliary Hydraulic Pressure		239.59 bar	
High-Flow Auxiliary Hydraulics – Option		114 l/min	
High-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar	
Tank capacities			
Fueltank		106 l	
Reservoir Capacity Hydraulics		22.70 l	
Displacement		3.30 l	
Displacement		J.JU (





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend