Technical sheet:

2750V






	2750v Created	2750V Created on December 14, 2025 at 5:52 PM UTC	
Capacities		Imperial	
Operating Capacity At 50% Tipping Load		2750 lb	
Operating Weight		8199 lb	
Unladen weight		7553 lb	
Tipping capacity		5501 lb	
Weight and dimensions			
Wheelbase	у	48 in	
Overall Operating Height - Fully Raised	h27	167 in	
Height to Hinge Pin - Fully Raised	h28	129 in	
Overall Height to top of ROPS	h17	81 in	
Dump angle at full height	a5	42 °	
Dump height	h29	98 in	
Overall length with bucket	I16	150 in	
Dump reach - Full height	r6	33 in	
Rollback Angle at Full Height	a4	92 °	
Seat to ground height	h30	39 in	
Overall width less bucket	b1	67 in	
Ground clearance	m4	9 in	
Overall length - Less Bucket	12	119 in	
Clearance Radius - Front with Bucket	b18	90 in	
Rear departure angle	510	30 °	
Performances		30	
Travel speed (unladen)		7 mph	
Travel Speed with Two-Speed Option - Maximum		7 mph	
Wheels		т тири	
Transmission type		Hydrostatic	
Engine		,	
Engine brand		Yanmar	
Engine model		4TNV98CT-XNGL	
Engine norm		Tier 4	
Max. torque / Engine rotation		217 ft/lbs / 1800 rpm	
Power source		Diesel	
Number of cylinders		4	
Engine power (Hp / kW)		72 Hp / 52.70 kW	
Engine cooling system		Water	
Battery voltage		12 V	
Alternator - Ampere		100 A	
Starter		3 kW	
Hydraulics		<u> </u>	
Standard flow - Auxiliary hydraulics		26 US gpm	
Auxiliary Hydraulic Pressure		gp	
		3475 PSI	
• •		3475 PSI 33 US apm	
High-Flow Auxiliary Hydraulics - Option		33 US gpm	
High-Flow Auxiliary Hydraulics - Option High-Flow Auxiliary Hydraulics Pressure - Option			
High-Flow Auxiliary Hydraulics - Option High-Flow Auxiliary Hydraulics Pressure - Option Tank capacities		33 US gpm 3325 PSI	
High-Flow Auxiliary Hydraulics - Option High-Flow Auxiliary Hydraulics Pressure - Option Tank capacities Fuel		33 US gpm 3325 PSI 28 US gal	
High-Flow Auxiliary Hydraulics - Option		33 US gpm 3325 PSI	

2750V - Dimensional drawing











Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes