

Technical sheet :

1900R NXT2



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Imperial
Operating Capacity At 50% Tipping Load		1900 lb
Operating Weight		6995 lb
Weight and dimensions		Imperial
Wheelbase	y	42 in
Overall Operating Height - Fully Raised	h27	153 in
Height to Hinge Pin - Fully Raised	h28	119 in
Overall Height to top of ROPS	h17	77 in
Dump angle at full height	a5	38 °
Dump height	h29	94 in
Overall length with bucket	l16	128 in
Dump reach - Full height	r6	23 in
Rollback at ground	a13	28 °
Rollback Angle at Full Height	a4	99 °
Seat to ground height	h30	36 in
Overall width less bucket	b1	62 in
Bucket Width	e1	66 in
Ground clearance	m4	6 in
Overall length - Less Bucket	l2	96 in
Clearance Radius - Front with Bucket	b18	80 in
Rear departure angle		21 °
Performances		Imperial
Travel speed (unladen)		8 mph
Travel Speed with Two-Speed Option - Maximum		12 mph
Wheels		Imperial
Standard tires		10 x 16.5
Engine		Imperial
Engine brand		Yanmar
Engine model		4TNV98C-NMS2V
Engine norm		Stage IV, Tier 4 final
Max. torque / Engine rotation		178 ft/lbs / 1625 rpm
Power source		Diesel
Engine power (Hp / kW)		69.30 Hp / 51 kW
Battery voltage		12 V
Starter		3 kW
Hydraulics		Imperial
Standard flow - Auxiliary hydraulics		19 US gpm
Auxiliary Hydraulic Pressure		3002 PSI
High-Flow Auxiliary Hydraulics - Option		30 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		2596 PSI
Tank capacities		Imperial
Fuel		16 US gal
Hydraulic tank capacity		9 US gal
Noise and vibration		Imperial
Noise to environment (LwA)		100 dB
Whole-Body Vibration (ISO 2631-1)		3 ft/s ²
Vibration on hands/arms		< 5 ft/s ²



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes