


Technical sheet :

1900R NXT2



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric	
Operating Capacity At 50% Tipping Load		861.82 kg	
Operating Weight		3172.87 kg	
Weight and dimensions			
Wheelbase	y	1066.80 mm	
Overall Operating Height - Fully Raised	h27	3886.20 mm	
Height to Hinge Pin - Fully Raised	h28	3022.60 mm	
Overall Height to top of ROPS	h17	1955.80 mm	
Dump angle at full height	a5	38 °	
Dump height	h29	2387.60 mm	
Overall length with bucket	l16	3251.20 mm	
Dump reach - Full height	r6	584.20 mm	
Rollback at ground	a13	28 °	
Rollback Angle at Full Height	a4	99 °	
Seat to ground height	h30	904.24 mm	
Overall width less bucket	b1	1574.80 mm	
Bucket Width	e1	1676.40 mm	
Ground clearance	m4	160.02 mm	
Overall length - Less Bucket	l2	2446.02 mm	
Clearance Radius - Front with Bucket	b18	2032 mm	
Rear departure angle		21 °	
Performances			
Travel speed (unladen)		12.55 km/h	
Travel Speed with Two-Speed Option - Maximum		19.47 km/h	
Wheels			
Standard tires		10 x 16.5	
Engine			
Engine brand		Yanmar	
Engine model		4TNV98C-NMS2V	
Engine norm		Stage IIIA	
Max. torque / Engine rotation		241 Nm / 1625 rpm	
Power source		Diesel	
Engine power (Hp / kW)		69.30 Hp / 51 kW	
Battery voltage		12 V	
Starter		3 kW	
Hydraulics			
Standard flow - Auxiliary hydraulics		70.78 l/min	
Auxiliary Hydraulic Pressure		207 bar	
High-Flow Auxiliary Hydraulics - Option		113.94 l/min	
High-Flow Auxiliary Hydraulics Pressure - Option		179 bar	
Tank capacities			
Fuel		58.67 l	
Hydraulic tank capacity		35.96 l	
Noise and vibration			
Noise to environment (LwA)		100 dB	
Whole-Body Vibration (ISO 2631-1)		0.96 m/s ²	
Vibration on hands/arms		1.53 m/s ²	

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes