


Technical sheet :

1950RT



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Imperial
Operating Weight		8400 lb
Unladen weight		7544 lb
Operating Capacity At 50% Tipping Load		2787 lb
Tipping capacity		5571 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	158 in
Height to Hinge Pin - Fully Raised	h28	120 in
Dump reach - Full height	r6	26 in
Dump angle at full height	a5	39 °
Overall length with bucket	l16	129 in
Departure angle	a2	27 °
Ground clearance	m4	7 in
Overall width less bucket	b1	69 in
Bucket Width	e1	70 in
Clearance Radius - Front with Bucket	b18	81 in
Engine		
Engine brand		Yanmar
Engine model		4TNV98C-NMS2V
Engine power (Hp)		69 Hp
Engine power (kW)		51.70 kW
Max. torque / Engine rotation		178 ft/lbs @ 2500 rpm
Battery voltage		12 V
Accessory plug		120 V
Alternator - Ampere		100 A
Transmission		
Transmission type		Hydrostatic
Hydraulics		
Standard flow - Auxiliary hydraulics		18 US gpm
Auxiliary Hydraulic Pressure		3249 PSI
High-Flow Auxiliary Hydraulics - Option		32 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		2901 PSI
Tank capacities		
Hydraulic tank capacity		10 US gal
Fuel		16 US gal
Cooling liquid		3 US gal
Displacement / Number of cylinders		0.87 US gal / 4
Noise and vibration		
Noise to environment (LwA)		101.40 dB
Noise at driving position (LpA)		82 dB
Whole-Body Vibration (ISO 2631-1)		4 ft/s ²

**Head Office**

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes