

Technical sheet :

1950RT



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric
Rated Operating Capacity		885 kg
Rated Operating Capacity with Optional Counterweight		2657 kg
Operating Weight		3697 kg
Unladen weight		3422 kg
Operating Capacity At 50% Tipping Load		1264 kg
Tipping capacity		2527 kg
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	4018 mm
Height to Hinge Pin - Fully Raised	h28	3048 mm
Dump reach - Full height	r6	648 mm
Dump angle at full height	a5	39 °
Overall length with bucket	l16	3279 mm
Departure angle	a2	27 °
Ground clearance	m4	188 mm
Overall width less bucket	b1	1746 mm
Bucket Width	e1	1778 mm
Clearance Radius - Front with Bucket	b18	2063 mm
Engine		
Engine brand		Yanmar
Engine model		4TNV98C-NMS2V
Gross Power		51.70 kW
Net Power		51 kW
Max. torque / Engine rotation		241 Nm @ 2500 rpm
I.C. Engine power rating - Power		68.40 Hp / 51 kW
Battery voltage		12 V
Accessory plug		120 V
Alternator - Ampere		100 A
Transmission		
Transmission type		Hydrostatic
Hydraulics		
Standard flow - Auxiliary hydraulics		71 l/min
Auxiliary Hydraulic Pressure		380 bar
High-Flow Auxiliary Hydraulics - Option		113 l/min
High-Flow Auxiliary Hydraulics Pressure - Option		420 bar
Tank capacities		
Hydraulic tank capacity		36 l
Fuel tank		58.70 l
Liquid cooling tank volume		12.90 l
Displacement / Number of cylinders		3.30 l / 4
Noise and vibration		
Noise to environment (LwA)		101.40 dB
Noise at driving position (LpA)		82 dB
Whole-Body Vibration (ISO 2631-1)		1.10 m/s ²



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes