


Technical sheet :

1950RT



 **MANITOU**
HANDLING YOUR WORLD

Capacities		Metric	
Operating Weight		3810 kg	
Unladen weight		3422 kg	
Operating Capacity At 50% Tipping Load		1264 kg	
Tipping capacity		2527 kg	
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	4018 mm	
Height to Hinge Pin - Fully Raised	h28	3048 mm	
Dump reach - Full height	r6	648 mm	
Dump angle at full height	a5	39 °	
Overall length with bucket	l16	3279 mm	
Departure angle	a2	27 °	
Ground clearance	m4	188 mm	
Overall width less bucket	b1	1746 mm	
Bucket Width	e1	1778 mm	
Clearance Radius - Front with Bucket	b18	2063 mm	
Engine			
Engine brand		Yanmar	
Engine model		4TNV98C-NMS2V	
Engine power (Hp)		69 Hp	
Engine power (kW)		51.70 kW	
Max. torque / Engine rotation		241 Nm @ 2500 rpm	
Battery voltage		12 V	
Accessory plug		120 V	
Alternator - Ampere		100 A	
Transmission			
Transmission type		Hydrostatic	
Hydraulics			
Standard flow - Auxiliary hydraulics		70 l/min	
Auxiliary Hydraulic Pressure		224 bar	
High-Flow Auxiliary Hydraulics - Option		120 l/min	
High-Flow Auxiliary Hydraulics Pressure - Option		220 bar	
Tank capacities			
Hydraulic tank capacity		36 l	
Fuel		58.70 l	
Cooling liquid		12.90 l	
Displacement / Number of cylinders		3.30 l / 4	
Noise and vibration			
Noise to environment (LwA)		101.40 dB	
Noise at driving position (LpA)		82 dB	
Whole-Body Vibration (ISO 2631-1)		1.10 m/s ²	



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes