Technical sheet :

MTA 1242 MAX





ITA 1242 MAX	Created on August	13, 2025	at 12:29	AM UTC

	мта 1242 мах Created on August 13, 2025 at 12:29 AM
Capacities	Metric
Max. capacity	5443.10 kg
Max. lifting height	12.96 m
Maximum outreach	8.69 m
Weight and dimensions	
Overall length to carriage	l11 6.30 m
Overall length (with forks)	l1 7.51 m
Overall width	b1 2.54 m
Overall height	h17 2.47 m
Wheelbase	y 3.50 m
Ground clearance	m4 0.48 m
Overall cab width	b4 0.95 m
Tilt-up angle	a4 34 °
Tilt-down angle	
-	
External turning radius	Wa3 3.88 m
Overall weight	12836.66 kg
Tires type	Pneumatic
Forks length / width / section	l / e / s 1219 mm x 152 mm x 63.50 mm
Frame leveling longitudinal +/-	10 °
Performances	
Lifting	16 s
Lowering	11 s
Extension	17 s
Retraction	12 s
Crowd	4 s
Dump	б s
Engine	
Engine brand	Deutz
Engine norm	Tier 4 final
Engine model	TCD 3.6 L4
Number of cylinders / Capacity of cylinders	4 - 3600 cm ³
I.C. Engine power rating - Power	127 Hp / 95 kW
Max. torque / Engine rotation	500 Nm @ 2300 pm
Transmission	
Transmission type	Powershift
Number of gears (forward / reverse)	5/3
Max. travel speed	36.20 km/h
Parking brake	Hydraulic spring release SAHR
Service brake	Wet disc brakes
Hydraulics	
Hydraulic pump type	Axial piston
Hydraulic flow / Pressure	151 l/min-275.80 bar
Tank capacities	
Engine oil	8.51
Hvdraulic oil	143.80
Diesel Exhaust fluid (AdBlue® type)	15.141
Fuel tank	1441
Noise and vibration	
Noise at driving position (LpA)	80 dB
Miscellaneous	
Steering wheels (front / rear)	2/2



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes