

RS6-34 GEN:3

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ Four-wheel Drive/Four-wheel steer
- ✓ Transportable at 15,000 lbs.
- ✓ Frame leveling 10° left / 10° right
- ✓ Ideal rental product for jobsites up to three stories

Key Specifications

- ✓ 6,000 lbs. (2722 kg) maximum lift capacity
- ✓ 34' 3" (1.4 m) maximum lift height
- ✓ 4,000 lbs. (1815 kg) lift capacity to 34' 3" (10.4 m)
- ✓ 74 hp (55 kW) Deutz diesel engine

SPECIFICATIONS

		IMPERIAL
Capacities	Max. capacity	6000 lb
	Max. lifting height	34 ft 3 in
	Max. outreach	23 ft
Weight and dimensions	Overall length to carriage	16 ft
	Length to face of forks	16 ft 1 in
	Overall width	7 ft 10 in
	Overall height	7 ft 9 in
	Wheelbase	9 ft 2 in
	Ground clearance	14 in
	External turning radius	12 ft 6 in
	Unladen weight	15102 lb
	Overall weight	15113 lb
	Standard tires	15 x 19.5
	Frame leveling longitudinal +/-	10 °
Engine	Engine brand	Deutz
	Engine norm	Stage IV / Tier 4 Final
	Engine model	TD 3.6 L4
	I.C. Engine power rating - Power	74 Hp / 55 kW
	Max. torque / Engine rotation	243 ft/lbs @ 2500 rpm
Transmission	Transmission type	Torque converter with powershift gearbox
	Number of gears (forward / reverse)	3 / 3
	Max. travel speed	18 mph
	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
Hydraulics	Axle Manufacturer	Dana
	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	29 US gpm-3002 PSI
Tank capacities	Hydraulic oil	29 US gal
	Fuel tank	29 US gal
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Safety cab homologation	ROPS/FOPS
	Controls	Single Joystick FNR



STANDARD FEATURES

- Crab mode
- 3 speeds
- Storage box behind the seat
- Wet disc brakes
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Glowplugs Starter Assist
- Multi-Function Display Screen

OPTIONAL FEATURES

- Suspension Seat
- Light Package - LED
- Solid Rubber Tires
- Foam Filled Tires
- Enclosed Cab with Heat and Defrost
- PWP System 3-Section Boom
- Enclosed Cab with Heat and A/C
- Easy Manager

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT