RS

RS6-34 GEN:3




GEHL.

| pacities x. capacity x. lifting height x. outreach sight and dimensions erall length to carriage ngth to face of forks erall width erall height heelbase bound clearance lerenal turning radius laden weight erall weight nuclard tires lame leveling longitudinal +/- gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation lunsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | l11 l2 b1 h17 y m4 Wa3 | Imperial 6000 lb 34 ft 3 in 23 ft 16 ft 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
|--|--|--|
| x. lifting height x. outreach ight and dimensions erall length to carriage night to face of forks erall width erall height heelbase bund clearance bernal turning radius laden weight erall weight hundard tires hunder dires gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation hunsmission hunsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | l2 b1 h17 y m4 | 34 ft 3 in 23 ft 16 ft 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 |
| x. outreach ight and dimensions erall length to carriage ngth to face of forks erall width erall height neelbase ound clearance beenal uring radius laden weight erall weight andard tires ame leveling longitudinal +/- gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | l2 b1 h17 y m4 | 23 ft 16 ft 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| erall length to carriage ngth to face of forks erall width erall height heelbase bund clearance | l2 b1 h17 y m4 | 16 ft 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 |
| erall length to carriage ngth to face of forks erall width erall height neelbase bund clearance ternal turning radius laden weight erall weight and rives ame leveling longitudinal +/- gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation ansmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | l2 b1 h17 y m4 | 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 |
| ngth to face of forks erall width erall height neelbase bund clearance ternal turning radius laden weight erall weight andard tires time leveling longitudinal +/- gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation timsmission timsmission timsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | l2 b1 h17 y m4 | 16 ft 1 in 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 |
| erall width erall height neelbase bund clearance cernal turning radius laden weight erall weight and ard tires ame leveling longitudinal +/- gine gine brand gine model Engine power rating - Power x. torque / Engine rotation ansmission ansmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | b1 h17 y m4 | 7 ft 10 in 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| erall height neelbase bund clearance sernal turning radius laden weight erall weight undard tires me leveling longitudinal +/- gine gine brand gine norm gine power rating - Power x. torque / Engine rotation unsmission unsmission unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | h17 y m4 | 7 ft 9 in 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| neelbase bund clearance ternal turning radius laden weight erall weight undard tires une leveling longitudinal +/- gine gine brand gine norm gine norm gine power rating - Power x. torque / Engine rotation unsmission unsmission unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | y m4 | 9 ft 2 in 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| cound clearance dernal turning radius laden weight erall weight undard tires dere leveling longitudinal +/- gine gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | m4 | 14 in 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| ternal turning radius laden weight erall weight undard tires time leveling longitudinal +/- gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | 12 ft 6 in 15102 lb 15113 lb 15 x 19.5 10 ° |
| laden weight erall weight indard tires ime leveling longitudinal +/- gine gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | Wa3 | 15102 lb 15113 lb 15 x 19.5 10 ° |
| erall weight andard tires ame leveling longitudinal +/- gine gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | 15113 lb 15 x 19.5 10 ° |
| andard tires ame leveling longitudinal +/- gine gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | 15 x 19.5 10 ° |
| ame leveling longitudinal +/- gine gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation ansmission ansmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | 10 ° |
| gine gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | |
| gine brand gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | Deutz |
| gine norm gine model Engine power rating - Power x. torque / Engine rotation unsmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | Deutz |
| gine model Engine power rating - Power x. torque / Engine rotation ansmission ansmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | |
| Engine power rating - Power x. torque / Engine rotation susmission unsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | Stage IV / Tier 4 Final |
| x. torque / Engine rotation Insmission Insmission type Insmis | | TD 3.6 L4 |
| Insmission Insmission type Ins | | 74 Hp / 55 kW |
| nsmission type mber of gears (forward / reverse) x. travel speed rking brake vice brake | | 243 ft/lbs @ 2500 rpm |
| mber of gears (forward / reverse) x. travel speed rking brake vice brake | | |
| x. travel speed rking brake vice brake | | Torque converter with powershift gearbox |
| x. travel speed rking brake vice brake | | 3 / 3 |
| vice brake | | 18 mph |
| vice brake | | SAHR |
| | | Wet disc brakes |
| le Manufacturer | | Dana |
| draulics | | |
| draulic pump type | | Gear pump |
| draulic flow / Pressure | | 29 US gpm-3002 PSI |
| nk capacities | | |
| draulic oil | | 29 US gal |
| el tank | | 29 US gal |
| scellaneous | | 3 |
| pering wheels (front / rear) | | 2 / 2 |
| ve wheels (front / rear) | | 2 / 2 |
| rety cab homologation | | ROPS/FOPS |
| ntrols | | Single joystick with FNR |

RS6-34 GEN:3 - Load chart

Machine on tyres with forks Imperial







Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend